ت	т	п	D		0		► ►		٦
					LAYOUT SHO	OWN AS EXAMPLE			
	Keying Shown as	example							
CHARACTERISTICS		Connector dimension							
Standard : Based on MIL-DTL-38999 Series III	_	Dim Nominal ØS 25 Max							
-Shell Material : Composite -Shell Plating : Without Plating -Insulator : Thermoplastic -Contacts : Copper Alloy	E	Z 31 Max VV THREAD M15x1-6g			due to a use of the Pro the Specifications issued by	ble for any non-conformity o oducts which does not comp y either of the Parties or by a mmendation, technical notic	ly with third party		
-Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer						Country Jurisdicti	on & Control List	]	
-Contact Plating : Gold over copper Alloy 0.8µm minimum							lot Listed		
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				PN: 8D511X01PC					
-Temperature Range : -65°C to +175°C			A	18-10-2016	First Release			]	_
-Salt Spray : 2000 hours									
Mass : 12.8 g ± 10%			ISS Designed	DATE d By:	Latest modification - by Date:			MOD N°	-
			т	ITLE	Composite Plug 8D series				
BASIC SERIES: 8D 5 - 11 X SHELL TYPE : Plug with RFI Shielding	01 P C		SCAL	-		al linear rances: ±	NPRDS / PROJECT 859		_
CONTACT TYPE : Standard Crimp Contact		ORIENTAT		JRIAU			This document is the prop SOURIAU it must not be reproduc		
SHELL SIZE : 11		CONTACT TYPE : PIN(500 M					communicated without per		
		CONTACT LAYOUT	:11-01 FORMA	AT	SOU	IRIAU DRG N°		SHEET	
PLATING : X = Without Plating			A3			511X01PC-C		1/2	

	<b>工</b>	G	וד	т	D	0
		Contact Layout				
4		01				
		1#12 11-01	٦			
ω	Ctc A	X Y 0 0				
	-					SOURIAU shall not be liable for any due to a use of the Products wh
0						the Specifications issued by either of (professional recommendat Countr FR
					A 18-10-201 ISS DATE Designed By:	PN: 8D511) 16 First Release Latest modification - by Date:
_					SCALE	General linear Tolerances:
					SOURIAL	J WWW.SOURIAU.C
	н	G	F	E	FORMAT A3	SOURIAU 8D511X0
		· • •				✓ 1

