-	I	۵	П	m	ţ		C	σ	A		
4	R 22.6 Max		Keying Shown as	s example			Image: constraint of the second sec	HOWN AS EXAMPLE			4
N	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Serie -Shell Material : Aluminium -Shell Material : Aluminium -Shell Plating : Black Zinc Nicket -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomet -Contact Plating : Gold over copper -Durability : 500 Mating cycle -Delivered with Souriau contacts and Acce -Temperature Range : -Temperature Range : -65°C to +175°C	el er er Alloy 0.8µm minimum les cessories		Connector dimension Dim Nominal A 34.9±0.3 B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 VV THREAD M15x1-6g		A 01-10-201	due to a use of the the Specifications issued (professional re		ly with a third party		2
	-Salt Spray : 500 hours -Mass : 17.99 g ± 10%					ISS DATE Designed By: TITLE SCALE		uminium Receptacle	SUSTOMER DRAWING 8D series	MOD N°	
	BASIC SERIES:8DSHELL TYPE : Jam nut ReceptacleCONTACT TYPE : Standard Crimp ContaSHELL SIZE : 11PLATING : Z = Black Zinc Nickel		Z 04 P D	ORIEN CONTACT TYPE : PIN(50 CONTACT LAYC		NA SOURIAU FORMAT A3	J WWW.SOL SO	JRIAU.COM URIAU DRG N°	NPRDS / PROJECT 859 This document is the prop SOURIAU it must not be reproduc communicated without pe	rmission SHEET	1
	Н	G	F	E	1	A3 D	C	D711Z04PD-C	A	1/2	

Г	D I	т (Г		B	
4	Contact Layout $ \begin{array}{c} & & & \\ & & \\$		Panel cutout JAM NUT RECEPTACLE (TYPE 7)		4
	$\begin{tabular}{ c c c c c c c c c c c c c c c c c c c$		Dim Nomir	nal	
ω			B 19.59+0/ ØC 20.96+0.2	/-0.25	3
			due to a use of the P the Specifications issued	iable for any non-conformity or damage Products which does not comply with by either of the Parties or by a third party commendation, technical notice.)	
N			A 01-10-2016 First Release	BD711Z04PD	2
			ISS DATE Latest modification - by	MOD N°	
			Designed By: Date: TITLE Alu	customer drawing uminium Receptacle 8D series	
-				Ierances: NPRDS / PROJECT ± 859 This document is the property of SOURIAU	1
				communicated without permission	
		1		URIAU DRG N° SHEET 0711Z04PD-C 2/2	
L	H G I	F E	DC	B A]