



Click [here](#) for the 3D model.

| Dimensions |                    |
|------------|--------------------|
| L          | 7.37mm +/-0.25mm   |
| H          | 7.37mm +/-0.25mm   |
| T          | 2.29mm +/-0.25mm   |
| S          | 5.08mm +/-0.38mm   |
| LL         | 31.75mm MIN        |
| F          | 0.635mm +/-0.051mm |

| Packaging Specifications |           |
|--------------------------|-----------|
| Packaging                | Bulk, Bag |
| Packaging Quantity       | 100       |

| General Information     |  |
|-------------------------|--|
| Series                  | GR900  |
| Style                   | Radial   |
| RoHS                    | No   |
| Prop 65                 | <b>⚠ WARNING:</b> Cancer and reproductive harm - <a href="http://www.p65warnings.ca.gov">http://www.p65warnings.ca.gov</a> . |
| SCIP Number             | 8c864fd1-202b-4ce7-85fd-56c9e19121ad   |
| Termination             | Lead (SnPb)  |
| Failure Rate            | N/A  |
| Testing and Reliability | GR900 CSAM Group A   |
| AEC-Q200                | No   |
| Notes                   | Lead Length Shown Is For Parts Supplied In Bulk, See Packaging Specifications For Lead Lengths When Not Provided In Bulk.    |

| Specifications                  |            |
|---------------------------------|------------|
| Capacitance                     | 0.22 uF    |
| Capacitance Tolerance           | 20%        |
| Voltage DC                      | 100 VDC    |
| Dielectric Withstanding Voltage | 250 VDC    |
| Temperature Range               | -55/+125°C |
| Temperature Coefficient         | BX         |
| Dissipation Factor              | 2.5%       |
| Insulation Resistance           | 4.5 GOhms  |