

6

5


4

3

2

1

MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGTH
1200980206	MP3G62PP4M010	1.0M +55.6mm -0 [3.28' +2.19" -0]
1200980154	MP3G62PP4M050	5.0M +165.1mm -0 [16.40' +6.50" -0]



VOLTAGE RATING	250 VAC/VDC
AMPERAGE RATING	4 AMPS
PROTECTION FOR D-SUB	IP40
OPERATING TEMPERATURE - D-SUB	0°C TO 60°C

ITEM	COMPONENT	MATERIAL	FINISH
1	D-SUB	ABS	BLACK
2	CABLE- 22 AWG, COPPER STRANDING TWISTED PAIR, SHIELD WITH BRAID	PUR	PURPLE
3	LABEL	MLYAR	BLACK/YELLOW

RELEASED DRAWING
EC NO: WEL2010-0081
DRWN: LHARTMAN 8/27/09
CHKD: BWOODMAN 09/08/27
APPR: JFMURPHY 2009/08/28

QUALITY SYMBOLS
▽=0
∇=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	±----	±----
3 PLACES	±----	±----
2 PLACES	±----	±.01
1 PLACE	±0.3	±----

ANGULAR ±----°

DRAFT WHERE APPLICABLE
MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE IN/MM

SCALE NTS

DESIGN UNITS INCH

THIRD ANGLE PROJECTION

DRAWN BY DATE
LHARTMAN 2009/08/27

CHECKED BY DATE
BWOODMAN 2009/08/27

APPROVED BY DATE
JFMURPHY 2009/08/27

MATERIAL NO.

SIZE A

TITLE

D-SUB PROFIBUS VERT TO D-SUB(2) HORZ
#22/2 SHLD PURPLE PUR

MOLEX INCORPORATED

DOCUMENT NO. SD-120098-020

SHEET NO. 1 OF 1

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

6

5

4

3

2

1