	۳ D	m	D C B A	Π				
4								
	Keyin CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	ng Shown as example Connector dimension Dim Nominal						
2	-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cycles	A 34.9±0.3 B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 VV THREAD M15x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) $Country Jurisdiction \& Control List \\\hline FR \qquad Not Listed \\\hline PN: 8D711F98AC$	2				
	-Delivered with Souriau contacts and Accessories-Temperature Range: -65°C to +200°C-Salt Spray: 48 hours-Mass: 17.89 g ± 10%		A 30-09-2016 First Release MOD N° ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING	_				
	BASIC SERIES: 8D 7 - 11 F 98 A SHELL TYPE : Jam nut Receptacle	C CONTACT TYPE : PIN(500 Matings) CONTACT LAYOUT : 11-98	SOURIAU VV VV.SOURIAU.COIVI it must not be reproduced or communicated without permission 8 FORMAT SOURIAU DRG N° SHEET	1				
	H G F	E	A3 8D711F98AC-C 1/2 D C B A					

Constitution For Constitution For Constitution 4 Image: Constitution Image: Constitution Image: Constitution 1mage: Constitititititie 1mage: Constituti	г	т	Q	т	т	D	0	σ	A		
Image: Source interview Image: Source interview <th>4</th> <th>-×</th> <th>$E \bigoplus E \bigoplus E \bigoplus B \bigoplus E \bigoplus E \bigoplus E \bigoplus E \bigoplus E \bigoplus E \bigoplus$</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>4</th>	4	-×	$E \bigoplus E \bigoplus E \bigoplus B \bigoplus E \bigoplus E \bigoplus E \bigoplus E \bigoplus E \bigoplus E \bigoplus $								4
a a as based 0.025 grd as based 0.025/0.05 as based 0.025/0.05 SOURIAU shall not be liable for any rem conformity or dornage that based of the Product's which dates not comply with the Socializations based by their based to be shall be based to be based by their based by the based		size Not	Jon (mm) X-axis (mm) Y-axis (mm) 4 000 (0.00) +.130 (3.30) +.130 (3.30) +.000 (0.00) +.065 (1.65) 113 (2.87) 055 (1.65) 113 (2.87) 130 (3.30) +.000 (0.00) +.000 (0.00) +.000 (0.00) er of Size contacts Service rating Contact location Supersedes				K>	<u>↓</u>			_
No	3						B 19.59+0/-0	.25			3
Image: No Image: FR Not Listed 2 PN: 8D711F98AC PN: 8D711F98AC Image: FR Image: FR<							due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party				
ISS DATE Latest modification - by MOD N* Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Receptacle 8D series SCALE General linear NPRDS / PROJECT NA Image: Sources: 859 ± This document is the property of SOURIAU SOURIAU WWW.SOURIAU.COM Source or communicated without permission FORMAT SOURIAU DRG N° SHEET	S						PN: 8[FR			2
SCALE NA General linear NPRDS / PROJECT 859 1 NA ± Tolerances: ± 859 1 SOURIAU WWW.SOURIAU.COM SOURIAU SOURIAU it must not be reproduced or communicated without permission FORMAT SOURIAU DRG N° SHEET						ISS DATE	Latest modification - by Date:		CUSTOMER DRAWING	IOD N°	_
SOURIAU WWW.SOURIAU.COM SOURIAU FORMAT SOURIAU DRG N° SHEET	<u> </u>					SCALE	Gener Toler	al linear ances:	NPRDS / PROJECT 859		1
AS 8D711F98AC-C 2/2						FORMAT	SOU	RIAU DRG N°	SOURIAU it must not be reproduced or communicated without permissi	on	
H G F E D C B A		Н	G	F	E			1		2/2	