SIEMENS

Data sheet

3SU1001-0AD50-0AA0-Z Y13



Indicator light in illuminated pushbutton design, 22 mm, round, plastic, blue, with laser labeling, symbol number according to, ISO 7000 or IEC 60417

product brand name	SIRIUS ACT
product designation	Indicator lights
design of the product	Actuating/signaling element
product type designation	3SU1
product line	Plastic, black, 22 mm
Enclosure	
number of command points	1
Actuator	
design of the actuating element	Illuminated pushbutton design
principle of operation of the actuating element	Fixed key
product extension optional	
light source	Yes
contact module	Yes
color of the actuating element	blue
material of the actuating element	plastic
shape of the actuating element	round
outer diameter of the actuating element	29.5 mm
marking of the actuating element	Customized labeling, graphical symbols acc. to ISO7000 and IEC60417
Front ring	
product component front ring	Yes
design of the front ring	Standard
material of the front ring	plastic
indicital of the noncing	pisotio
color of the front ring	black
color of the front ring	
color of the front ring General technical data	black
color of the front ring General technical data protection class IP	black IP66, IP67, IP69(IP69K)
color of the front ring General technical data protection class IP degree of protection NEMA rating	black IP66, IP67, IP69(IP69K)
color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance	black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13
color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27	black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms
color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373	black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms
color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373 vibration resistance	black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B
color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373 vibration resistance • acc. to IEC 60068-2-6	black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g
color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373 vibration resistance • acc. to IEC 60068-2-6 • for railway applications acc. to DIN EN 61373	black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B
color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373 vibration resistance • acc. to IEC 60068-2-6 • for railway applications acc. to DIN EN 61373 reference code acc. to IEC 81346-2	black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B
color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373 vibration resistance • acc. to IEC 60068-2-6 • for railway applications acc. to DIN EN 61373 reference code acc. to IEC 81346-2 Ambient conditions	black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B S

60721	
Installation/ mounting/ dimensions	
height	29.5 mm
width	29.5 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	11 mm
installation width	29.5 mm
installation depth	24.3 mm
Certificates/ approvals	
Further information	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1001-0AD50-0AA0-Z Y13

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1001-0AD50-0AA0-Z Y13

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1001-0AD50-0AA0-Z Y13

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1001-0AD50-0AA0-Z Y13&lang=en

last modified:

1/10/2021 🖸