



Main

Range	Square D X Series
Product or Component Type	Sensor
Device Application	Control
Device presentation	Complete product
Aesthetic name	X Series
Number of gangs	1 gang
Number of poles	1

Complementary

Switch Function	1-way
Sensor Type	PIR Light level sensor
[Ie] rated operational current AC	10 A
[Ue] rated operational voltage	120 V 277 V
Network type	AC
Network Frequency	60 Hz
Mounting Support	Ceiling
Device mounting	Surface
Material	Plastic housing
Color	White
Surface Finish	Matte
Width	4.53 in (115 mm)
Height	4.53 in (115 mm)
Depth	1.39 in (35.3 mm)
Quantity per Set	1 piece

Environment

Product Certifications	CULus ICES-003
Standards	UL 1917

Ordering and shipping details

Category	09933-WD SENSORS
Discount Schedule	DE9
GTIN	785901549246
Nbr. of units in pkg.	1
Package weight(Lbs)	4.34 oz (123.0 g)
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.89 in (4.8 cm)
Package 1 width	4.84 in (12.3 cm)
Package 1 Length	5.04 in (12.8 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	40
Package 2 Weight	13.05 lb(US) (5.92 kg)
Package 2 Height	10.83 in (27.5 cm)
Package 2 width	11.02 in (28 cm)
Package 2 Length	20.08 in (51 cm)
Unit Type of Package 3	PAL
Number of Units in Package 3	720
Package 3 Weight	267.99 lb(US) (121.56 kg)
Package 3 Height	47.24 in (120 cm)
Package 3 width	39.37 in (100 cm)
Package 3 Length	47.24 in (120 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: carbon black, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	2 year
----------	--------