08	ounting Option -#4-40 Unified Threaded Inserts	Contact Detail 500-Wire Hole .087x.013(2.2 .156 [3.96] Contact Spacing x	21x0.33) - Tail LG.=.282(7.16) : .140 [3.56] Row Spacing	THI! DO	IS IS A C.A.D. GENERATED DI NOT MAKE MANUAL REVISION	RAWING NS TO MA	STER	ISSUE NU ORIGIN	
	Card Slot Accepts — .054 (1.37) to .070 (1.78) Thick P.C. Board								
<u> </u>									
·	0.156[3.96]	5.936[150	0.77] ————						
	-	6.082 [15 <i>a</i> 6.368 [16							
								.38] Slot	
								0.330 [8.38] Card Slot	
	A								
1						-			
				-					
460[11.68]	A	6.678[169	9.62]				0.125[3.18]	SECTION	\ A-A
0.460		Point 305 / 315 / 355 Card Edge Connector Part Number: 305-074-500-508			t of Contact ACAD REFERENCE	NO. 305 EN	NG MASTER		
					DRAWN: J.LEE CHECKED:	DATE: SE			
	See Accompanying Page for: Mounting Options		EDAC INC TORONTO, ONTAR CANADA	ONTARIO AR SH	THESE DRAWINGS AND SPECIFICA ARE THE PROPERTY OF EDAC IN SHALL NOT BE REPRODUCED,OR OR USED AS THE BASIS FOR TH	INC.,AND R COPIED	SCALE: NTS DRAWING NUMBER		1 OF 2
- Woulding Options			YOUR CONNECTION TO QUALITY & SERV		MANUFACTURE OR SALE OF APPARATUS		305 Assembly		1

