т Q Т	m		0	₩ >		7
						4
<u>د</u>			LAYOUT SHOWN AS EXA	MPLE		3
Keying Shown as e	example					
CHARACTERISTICS						
-Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal					
-Shell Material : Aluminium	ØS 25 Max Z 31 Max		SOURIAU shall not be liable for any n	non-conformity or damage		
-Shell Plating : Black Zinc Nickel	VV THREAD M15x1-6g		due to a use of the Products which	h does not comply with		
-Insulator : Thermoplastic	the Constitutions issued by either of the Derties or by a third party					
-Contacts : Copper Alloy			(p	,		
-Seals & Grommet : Silicon Elastomer			Country FR	Jurisdiction & Control List Not Listed		
			FK	Not Listed	]	2
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories		PN: 8D511Z04BB				
						_
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 18-10-2016	First Release			
		ISS DATE	Latest modification - by		MOD N°	
		Designed By:	Date:	CUSTOMER DRAWING		
		TITLE Aluminium Plug 8D series				
BASIC SERIES: 8D 5 - 11 Z 04 B B		SCALE	General linear	NPRDS / PROJECT		_
→ SHELL TYPE : Plug with RFI Shielding		NA -	Tolerances:	859		4
			·	This document is the pro	perty of	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	ORIENTATION : B CONTACT TYPE : SOCKET(500 Matings)	SOURIAU	WWW.SOURIAU.CO	it must not be reprodu		
		FORMAT		communicated without p		_
PLATING : Z = Black Zinc Nickel	CONTACT LAYOUT : 11-04	A3	SOURIAU [		SHEET	
	7		8D511Z04	_	1/2	
H G F I	E \T	D	C	B A		

ſ	Ξ	۵ ا	г П	m	D	0		
		Contact Layout						
4	-X_	$ \begin{array}{ccc} \bullet & \bullet \\ \bullet & $						
	Shell Arrangement Numb	X-axis         Y-axis (mm)           +065 (165)         +065 (165)           +065 (165)         -065 (165)           -065 (165)         -065 (165)           -065 (165)         +065 (165)           -065 (165)         +065 (165)           -065 (165)         +065 (165)           -065 (165)         +065 (165)           -065 (165)         +065 (165)           -065 (165)         +065 (165)	]					
ω	11 -4 4	i 20 I All MS20050-4						
	+					SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recor	oducts w y either o	
N						PN: 80	Count FR	
					A 18-10-20 ISS DATE Designed By:	016 First Release Latest modification - by Date:		
<u> </u>					SCALE NA	Genera 	Alumin ral linear rances: ±	
					SOURIA	OURIAU WWW.SOURIAU.		
					FORMAT A3	SOU 8D	RIAL 511Z	
	Н	G	F	E	D	C		

