



Click [here](#) for the 3D model.

### Dimensions

|                |                    |
|----------------|--------------------|
| L              | 26mm -0.5mm        |
| H              | 14.5mm -0.5mm      |
| T              | 6mm -0.5mm         |
| S              | 22.5mm +0.6/-0.1mm |
| H <sub>0</sub> | 18.5mm +/-0.5mm    |
| F              | 0.8mm +/-0.05mm    |
| G              | 0.5mm NOM          |

### Packaging Specifications

|                    |                         |
|--------------------|-------------------------|
| Packaging          | Ammo, 360x340x59mm, Box |
| Packaging Quantity | 464                     |

### General Information

|                  |                          |
|------------------|--------------------------|
| Series           | F873                     |
| Dielectric       | Metallized Polypropylene |
| Style            | Radial                   |
| Features         | MKP EMI Safety           |
| RoHS             | Yes                      |
| Lead             | Wire Leads               |
| Safety Class     | X1                       |
| Qualifications   | ENEC, UL, cUL, CQC       |
| AEC-Q200         | No                       |
| THB Performance  | No                       |
| Component Weight | 2.681 g                  |
| Miscellaneous    | ClimCat: 40/110/56/B.    |
| Shelf Life       | 104 Weeks                |

### Specifications

|                       |              |
|-----------------------|--------------|
| Capacitance           | 0.01 uF      |
| Capacitance Tolerance | 10%          |
| Voltage AC            | 760 VAC (X1) |
| Voltage DC            | 1500 VDC     |
| Temperature Range     | -40/+110°C   |
| Rated Temperature     | 110°C        |
| Dissipation Factor    | 0.1% 1kHz    |
| Insulation Resistance | 30 GOhms     |
| Max dV/dt             | 300 V/us     |