Rev: 1 Last Update: 2017-04-25 21:32:09


Product Line: Tymphany **Product Description**

TC5FB00-08

Model No::

This TC family 1.5 inch 8 ohm full-range driver, with ferrite magnet, paper cone and PU surround, and steel basket, is designed to be a cost-effective high performance full range driver. The product was designed with portable and other compact applications in mind.


Mechanical Drawing




Specifications

DC Resistance	Revc	Ohms	6.74	5.0%	Energy Bandwidth Product	EBP	(1/Qes)*fs	
Minimum Impedance	Zmin	Ohms	7.52	7.5%	Moving Mass	Mms	g	0.5
Voice Coil Inductance	Le	mH	0.07		Suspension Compliance	Cms	um/N	775.9
Resonant Frequency	Fs	Hz	261.01	15%	Effective Cone diameter	D	cm	3.1
Mechanical Q Factor	Qms		3.84		Effective Piston Area	Sd	cm^2	7.6
Electrical Q Factor	Qes	2.81			Effective Volume	Vas	L	0.07
Total Q Factor	Qts		1.62		Motor Force Factor	BL	Tm	1.38
Ratio Fs/Qts	F	Fs/Qts	160.72		Motor Efficiency Factor	ß	(T*M^2)/Ohms	0.3
Half Space Sensitivity @2.83V	db@2.83V/1M	dB	79.36	+/- 1.0db	Voice coil former Material	VCfm		ASV
Half Space Sensitivity @1W/1M	db@1W/1M	dB	79.1	+/- 1.0db	Voice coil inner diameter	VCd	mm	16.28
Gap Height	Gh	mm	2		Rated Noise Power	P	W	5
Maximum Linear Excursion	Xmax	mm	0.6		Test Spectrum Bandwidth	250Hz-20KHz		
Ferrofluid Type	FF				Driver Size	Inch	1.5 in	
Driver Mass	Kg	0.06						

Frequency and Impedance Response



Tymphany HK LTD Address : Room 1307-8 Dominion Centre, 43-59 Queens Rd East, Wanchai, Hong Kong E-mail: sales@tymphany.com



Driver Specification Sheet