

# XXA30S2PM12

Ultrasonic sensors XX, ultrasonic sensor, stainless steel, cylindrical M30, angled, 2 m, PNP



## Main

|                               |   |
|-------------------------------|---|
| Range of Product              | Telemecanique Ultrasonic sensors XX   |
| Sensor Type                   | Ultrasonic sensor   |
| Series name                   | General purpose   |
| Sensor name                   | XXA   |
| Sensor design                 | Cylindrical M30   |
| Detection system              | Diffuse with 90° head)  |
| [Sn] nominal sensing distance | 6.56 Ft (2 m) adjustable with remote teach push-button<br>6.56 ft (2 m) software with kit |
| Material                      | Metal   |
| Type of output signal         | Discrete  |
| Discrete output function      | 1 NO or 1 NC programmable   |
| Wiring Technique              | 5-wire  |
| Discrete output type          | PNP   |
| [Us] rated supply voltage     | 12...24 V DC reverse polarity protection  |
| Electrical connection         | Male connector M12 5 pins   |
| [Sd] sensing range            | 0.51...6.56 ft (0.155...2 m)  |
| IP degree of protection       | IP65 conforming to IEC 60529<br>IP67  |

## Complementary

|   |   |
|---|---|
| Enclosure Material                                | Stainless steel 316L                                  |
| Front material                                    | Epoxy<br>Rubber<br>Resin                              |
| Supply voltage limits                             | 10...30 V DC  |
| Function Available                                | With synchronisation mode<br>Software configurable    |
| [Sa] assured operating distance                   | 0.51...6.56 ft (0.155...2 m) teach mode)              |
| Blind zone  | 6.10 in (155 mm)                                      |
| Transmission frequency                            | 120 kHz   |
| Repeat accuracy                                   | 0.1 %   |
| Deviation angle from 90° of object to be detected | -12...12 °  |
| Minimum size of detected object                   | Cylinder diameter 1 mm 4.59 ft (1.4 m)                |
| Status LED  | Output state 1 LED yellow)<br>Echo state 1 LED green) |
| Current Consumption                               | 65 mA   |
| Maximum switching current                         | 100 mA overload and short-circuit protection          |
| Maximum voltage drop                              | 2 V   |
| Switching frequency                               | 5.5 Hz  |
| Setting-up  | Teach mode<br>Configurator software                   |
| Maximum delay first up                            | 150 ms  |
| Maximum delay response                            | 90 ms   |
| Maximum delay recovery                            | 90 ms   |
| Marking   | CE  |
| Threaded length                                   | 2.94 in (74.7 mm)                                     |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|            |                       |
|------------|-----------------------|
| Height     | 1.18 in (30 mm)       |
| Width      | 1.18 in (30 mm)       |
| Depth      | 5.10 in (129.6 mm)    |
| Net Weight | 0.40 lb(US) (0.18 kg) |

## Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | EN/IEC 60947-5-2<br>CSA C22.2 No 14<br>UL 508 |
| Product Certifications                | CULus<br>E2<br>EAC<br>RCM<br>Ecolab           |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C)                    |
| Ambient Air Temperature for Storage   | -40...176 °F (-40...80 °C)                    |
| Vibration resistance                  | +/-1 mm 10...55 Hz)IEC 60068-2-6              |
| Shock resistance                      | 30 gn in all 3 axes 11 ms IEC 60068-2-27      |
| Resistance to electrostatic discharge | 8 kV IEC 61000-4-2                            |
| Resistance to electromagnetic fields  | 9.14 V/m (10 V/m) level 3 IEC 61000-4-3       |
| Resistance to fast transients         | 2 kV IEC 61000-4-4                            |

## Ordering and shipping details

|                       |   |
|-----------------------|---|
| Category              | 22489 - SENSORS XX ULTRASONIC GEN PURPOSE |
| Discount Schedule     | DS2                                       |
| GTIN                  | 3389119644778                             |
| Nbr. of units in pkg. | 1   |
| Package weight(Lbs)   | 8.47 oz (240 g)                           |
| Returnability         | Yes                                       |
| Country of origin     | US  |

## Packing Units

|                        |                  |
|------------------------|------------------|
| Unit Type of Package 1 | PCE              |
| Package 1 Height       | 5.12 in (13 cm)  |
| Package 1 width        | 1.61 in (4.1 cm) |
| Package 1 Length       | 3.74 in (9.5 cm) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|