
т	۵	п –	m	D	0







LAYOUT SHOWN AS

Keying Shown as example

CHARACTERISTICS

BASIC SERIES:

SHELL SIZE : 21

Н

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

PLATING : W = Olive drab Cadmium

ယ

 \sim

-Standard : Based on MIL-DTL-38999 Series III

-Shell Material	: Aluminium			
-Shell Plating	: Olive drab Cadmium			
-Insulator	: Thermoplastic			
-Contacts	: Copper Alloy			
-Seals & Grommet	: Silicon Elastomer			
-Contact Plating	: Gold over copper Alloy 0.8µm minimum			
-Durability	: 500 Mating cycles			
-Delivered without Souriau contacts				
-Temperature Range	- 65℃ to +175℃			
-Salt Spray	: 500 hours			

8D 0

G

21

W

72

S

F

A L

Dim	Nominal
Р	3.25±0.2
РР	4.93±0.2
R1	31.75
R2	29.36
S	39.7±0.3
V	20.07+0/-1.25
W	2.1/3.2
Z	31.5 Max
VV THREAD	M31x1-6g


Delivered W/O Contacts

CONTACT LAYOUT : 21-72

CONTACT TYPE : SOCKET(500 Matings)

Е

ORIENTATION : A





	Φ		A			
	-1				4	
1	6 (50					
Ľ	VUNDER VUNDER VUNDER VUNDER VUNDER VUNDER VUNDER	7				
	Con .					
		3				
		X				
	1					
S EXA	AMPLE				3	
	non-conformit					
er of t	which does not comply with r of the Parties or by a third party					
	on, technical n					
Intry R	Jurisd	iction & Cont Not Listed	rol List		2	
W	W72SAL					
					-	
				MOD N°		
		CUSTOMER	RDRAWING		-	
um	n Receptacle 8D series					
ar	NPRDS / PROJECT 859					
	This document is the property of					
J.COM SOURIAU it must not be reprod communicated without			t not be reproduc			
U I	DRG N°			SHEET	-	
N7	2SAL-C			1/2	J	
	В		A			

		۵	нт — — — — — — — — — — — — — — — — — — —	m	D	0
4		Contact Layout 72				Panel Cutou
_	Ctc	2#4 Power 6#16 21-72 X Y			¥	
ω	A B C D E F G H	0 6.19 8.5 4.3 6.25 0 8.5 -4.3 0 -6.19 -8.5 -4.3 -6.25 0 -8.5 4.3				Dim ØA ØA R1 ØT
						SOURIAU shall not be liable for any
N						due to a use of the Products wh the Specifications issued by either of (professional recommendati Country FR PN: 8D021W
_	-				A 03-11-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:
<u> </u>					SCALE NA	Aluminium General linear Tolerances: ±
					FORMAT A3	J WWW.SOURIAU.C SOURIAU 8D021W7
	Н	G	F	E	D	C

