ATGBICS FTLF1721P2BCL Finisar Compatible Transceiver SFP 2000Base-EX (1310nm, SMF, DOM, BiDi)

Brand : ATGBICS

Product code: FTLF1721P2BCL-C



Product name : FTLF1721P2BCL Finisar Compatible Transceiver SFP 2000Base-EX (1310nm, SMF, DOM, BiDi)

FTLF1721P2BCL Finisar Compatible Transceiver SFP 2000Base-EX (1310nm, SMF, DOM, BiDi)

ATGBICS FTLF1721P2BCL Finisar Compatible Transceiver SFP 2000Base-EX (1310nm, SMF, DOM, BiDi):

ATGBICS FTLF1721P2BCL 2000Base-EX supports a distance of up to over single mode fibre (SMF) using a wavelength of 1310nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Finisar FTLF1721P2BCL= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Power	
SFP transceiver type * Maximum data transfer rate * Interface type *	aximum data transfer rate *2670 Mbit/sterface type *SFPngle-mode fiber (SMF) supported✓ulti-mode fiber (MMF) supportedXber optic connectorLCFP transceiver standardEX'avelength1310 nmthernet LAN✓chernet interface typeGigabit Ethernet	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 0.8 W
Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector		Operational conditions Minimum operating temperature	-10 °C
SFP transceiver standard Wavelength Ethernet LAN Ethernet interface type		Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C -10 - 70 °C -40 - 85 °C 5 - 95% 5 - 95%
Digital Diagnostics Monitoring (DDM)	1	Weight & dimensions	
Wavelength-division multiplexing (WDM)	×	Width Depth	13.4 mm 56.5 mm
Features		Height	8.5 mm
Product colour	Silver	Weight	15 g
Housing material	Metal V V China Finisar CE, FCC, RoHS	Packaging data	
Plug and Play Hot-Plug support Hot-swap		Number of products included Package type	1 pc(s) Box
Easy to install		Technical details	
Country of origin Brand compatibility Certification		Sustainability compliance Sustainability certificates Doesn't contain	✔ RoHS Lead



5056468768063

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.