

Safe-IT USB-A to Lightning Sync/Charge Antibacterial Cable (M/M), MFi Certified, White, 1 m (3.3 ft.)

MODEL NUMBER: M100AB-01M-WH











USB/Lightning cable with antibacterial properties connects your Apple iPhone, iPad or iPod to the USB-A port on your computer or wall/car charger.

Features

USB Cable Charges and Syncs Your Latest-Generation iPhone, iPad and iPod

This Safe-ITTM sync/charge cable (M/M) connects your iPhone, iPad or iPod to the USB-A port on a computer, laptop, car charger or wall charger. It allows you to charge and power your Apple device, while simultaneously syncing and transferring photos, MP3s and other important files at USB 2.0 data transfer speeds up to 480 Mbps. The cable is backward compatible with previous USB generations, allowing you to use it with older equipment.

Antibacterial Properties Provide Extra Protection

The molded connectors and PVC jacket are constructed using an antibacterial material that is effective in inhibiting the growth of Escherichia coli (E. coli) and Staphylococcus aureus (staph). This added protection makes this cable an ideal solution for medical facilities, schools, businesses, restaurants/kitchens and anywhere else that needs extra protection against bacteria.

MFi-Certified for Broad Device Compatibility

The 5V 2.4A (12W max) Lightning cable is MFi-certified for use with the latest generation of iPhone, iPad and iPod devices. Integral strain relief gives the cable extra flexibility, reduces stress and helps the cable move freely without cracking or breaking loose from the connector.

Reversible Lightning Connector Attaches in Either Direction

Unlike traditional USB cables that connect in only one direction, the reversible 8-pin Lightning male connector plugs into an Apple device's port in either direction for an instant connection every time.

Specifications

OVERVIEW	
UPC Code	037332261045

Highlights

- MFi-certified for broad compatibility with your Apple iPhone, iPad or iPod
- Made with antibacterial material proven effective in inhibiting the growth of E. coli and staph
- Supports USB 2.0 speeds up to 480 Mbps to ensure reliable data transfers
- Reversible Lightning plug connects in either direction for immediate no-fuss use

Applications

- Charge and sync your Apple iPhone, iPad or iPod using the USB port on your computer or a wall charger up to 1 meter away
- Transfer photos and other important files between an external hard drive and your Apple device
- Provide extra protection against bacteria to give cable installers and IT personnel peace of mind during installation

System Requirements

- Computer, laptop or charger with USB-A port
- Most current iPhone, iPad and iPod devices

Package Includes

M100AB-01M-WH USB-A to Lightning Sync/Charge Antibacterial Cable (M/M), White, 1 m (3.3 ft.)



### Physical	Technology	Lightning; USB 2.0 (High Speed)	
Material of Construction PVC Cable Jacket Color White Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Length (IL) 3.7mm Cable Length (IL) 3.3 Cable Length (IL) 3.3 Cable Length (IL) 3.9.4 Shipping Dimensions (hwd / In.) 0.91 x 4.57 x 2.36 Shipping Dimensions (hwd / In.) 0.91 x 4.57 x 2.36 Shipping Weight (kg) 0.06 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing Power Provided to Connected 12W (5V/2.4A) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Contact Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS Antinscretial No <td< td=""><td>Cable Type</td><td>Passive</td></td<>	Cable Type	Passive	
Cable Jacket Color White Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Length (RL) 3.3 Cable Length (m) 1.01 Cable Length (m) 39.4 Shipping Dimensions (hwd / in.) 0.91 x 4.57 x 2.36 Shipping Weight (kg) 0.06 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range -40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing Power Provided to Connected Device(s) 12W (6V/2.4A) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Contact Plating Nickel Contact Plating Nickel Contact Plating Nickel Contact Plating No USB Specification USB 2.0 (up to 480 Mbps) Antimicrobial No USB	PHYSICAL		
Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Cuter Diameter (OD) 3.7mm Cable Length (ft.) 3.3 Cable Length (m) 1.01 Cable Length (in.) 39.4 Shipping Dimensions (twd / in.) 0.91 x 4.57 x 2.36 Shipping Weight (kg) 0.06 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing Power Provided to Connected Device(e) 12W (6V/2.4A) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel Contact Plating No USB Specification USB 2.0 (up to 480 Mbps)	Material of Construction	PVC	
Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 3.7mm Cable Length (ft.) 3.3 Cable Length (m) 1.01 Cable Length (in.) 39.4 Shipping Dimensions (twd / in.) 0.91 x 4.57 x 2.36 Shipping Weight (kg) 0.06 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing Power Provided to Connected 12W (6V/2.4A) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Platting Nickel Connector Platting Nickel Connector Specification No USB Specification USB 2.0 (up to 480 Mbps) Antimicrobial Yes STANDARDS & COMPLIANCE	Cable Jacket Color	White	
Cable Outer Diameter (OD) 3,7mm Cable Length (ft.) 3.3 Cable Length (m) 1.01 Cable Length (in.) 39.4 Shipping Dimensions (hwd / in.) 0.91 x 4.57 x 2.36 Shipping Weight (kg) 0.06 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range -40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 UGHTNING (MALE) Connector Plating Nickel Connector Plating Gold FEATURES & SPECIFICATIONS Antimicrobial No USB Specification USB 2.0 (up to 480 Mbps) Antimicactrial Yes STANDARDS & COMPLIANCE	Cable Jacket Material	PVC	
Cable Length (ft.) 3.3 Cable Length (m) 1.01 Cable Length (in.) 39.4 Shipping Dimensions (hwd / in.) 0.91 x 4.57 x 2.36 Shipping Weight (kg) 0.06 ENVIRONMENTAL Operating Temperature Range 32" to 113"F (0" to 45"C) Storage Temperature Range 40" to 158"F (-40" to 70"C) Operating Humidity Range 10% to 85% RH, Non-Condensing 5% to 90% RH, Non-Condensing Power Provided to Connected Device(s) 12W (5V/2.4A) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel Contact Plating Oid No USB 2.0 (up to 480 Mbps) Antimicrobial No USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Cable Jacket Rating	VW-1	
Cable Length (m) 1.01 Cable Length (in.) 39.4 Shipping Dimensions (hwd / in.) 0.91 x 4.57 x 2.36 Shipping Weight (kg) 0.06 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing ENVIRONMENTAL Storage Humidity Range 12W (5V/2.4A) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS Antimicrobial No USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Cable Outer Diameter (OD)	3.7mm	
Cable Length (In.) Shipping Dimensions (hwd / in.) O.91 x 4.57 x 2.36 Shipping Weight (kg) O.06 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range -40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing Power Provided to Connected 12W (5V/2.4A) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Contact Plating Gold FEATURES & SPECIFICATIONS Antinicrobial No USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Cable Length (ft.)	3.3	
Shipping Dimensions (hwd / in.) 0.91 x 4.57 x 2.36 Shipping Weight (kg) 0.06 ENVIRONMENTAL Operating Temperature Range 32" to 113"F (0" to 45"C) Storage Temperature Range 40° to 158"F (-40" to 70"C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing Power Provided to Connected 22W (5V/2.4A) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS Antimicrobial No USB Specification USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Cable Length (m)	1.01	
Shipping Weight (kg) ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing Power Provided to Connected Device(s) 22W (5V/2.4A) CONNECTIONS Side A - Connector 1 LIGHTNING (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS Antimicrobial No USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Cable Length (in.)	39.4	
ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range -40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing Power Provided to Connected Device(s) 2W (5V/2.4A) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS Antimicrobial No USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Shipping Dimensions (hwd / in.)	0.91 x 4.57 x 2.36	
Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range -40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85° RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing Power Provided to Connected 22W (5V/2.4A) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS Antimicrobial No USB Specification USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Shipping Weight (kg)	0.06	
Storage Temperature Range -40° to 158°F (-40° to 70°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing Power Provided to Connected Device(s) 12W (5V/2.4A) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS Antimicrobial No USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	ENVIRONMENTAL		
Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing Power Provided to Connected Device(s) 12W (5V/2.4A) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS Antimicrobial No USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Operating Temperature Range	32° to 113°F (0° to 45°C)	
Storage Humidity Range 5% to 90% RH, Non-Condensing Power Provided to Connected Device(s) 12W (5V/2.4A) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS Antimicrobial No USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Storage Temperature Range	-40° to 158°F (-40° to 70°C)	
Power Provided to Connected Device(s) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS Antimicrobial No USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Operating Humidity Range	10% to 85% RH, Non-Condensing	
CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS Antimicrobial No USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Storage Humidity Range	5% to 90% RH, Non-Condensing	
Side A - Connector 1 Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS Antimicrobial USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Power Provided to Connected Device(s)	12W (5V/2.4A)	
Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS Antimicrobial No USB Specification USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	CONNECTIONS		
Connector Plating Nickel Contact Plating Gold FEATURES & SPECIFICATIONS Antimicrobial No USB Specification USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Side A - Connector 1	USB A (MALE)	
Contact Plating Gold FEATURES & SPECIFICATIONS Antimicrobial No USB Specification USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Side B - Connector 1	LIGHTNING (MALE)	
FEATURES & SPECIFICATIONS Antimicrobial No USB Specification USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Connector Plating	Nickel	
Antimicrobial No USB Specification USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Contact Plating	Gold	
USB Specification USB 2.0 (up to 480 Mbps) Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	FEATURES & SPECIFICATIONS		
Antibacterial Yes STANDARDS & COMPLIANCE Product Certifications MFi	Antimicrobial	No	
STANDARDS & COMPLIANCE Product Certifications MFi	USB Specification	USB 2.0 (up to 480 Mbps)	
Product Certifications MFi	Antibacterial	Yes	
	STANDARDS & COMPLIANCE		
Dallo 05 (Farana), DEAGU 500 (USA)	Product Certifications	MFi	
Product Compilance Rohs; CE (Europe); REACH; FCC (USA)	Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	



WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	2-year limited warranty



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.