






THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By Tyco Electronics Japan G.K. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
J	-	D	REVISED	ECR-11-008701	26APR11	TS	KB



1. RECOMMENDED MOUNTING SCREW:  
 PAN-HEADED, TYPE 2 TAPPING SCREW OF  
 3DIA × 6LENGTH (JIS B1115, B1122),  
 TIGHTENING TORQUE: 0.39N·m MAX.  
 2. CIRCUIT NUMBER

1. 推奨取付ネジ: JIS B1115, B1112  
 タッピングネジ, なべ2種, 呼び径3, 長さ6,  
 締め付けトルク: 0.39N·m 以下  
 2. 回路番号



一般公差 (GENERAL TOLERANCE)

10 ≥	: ±0.2
30 ≥ > 10	: ±0.25
100 ≥ > 30	: ±0.3
ANGLE	: ±3°

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:
	0 PLC ± -
	1 PLC ± -
	2 PLC ± -
	3 PLC ± -
	4 PLC ± -
	ANGLES ± -
MATERIAL PBT	FINISH -

OBSOLETE	錫めっき (10) / 金めっき (2) PRE-TINED (10) / GOLD (2)	7, 9	△2	自然色 NATURAL	3-1123413-1
OBSOLETE	錫めっき (10) / 金めっき (2) PRE-TINED (10) / GOLD (2)	7, 9	△2	自然色 NATURAL	2-1123413-1
	錫めっき (12) PRE-TINED (12)	-		自然色 NATURAL	1123413-1
	タブ仕上 (本数) FINISH OF CONTACT			金めっき端子使用回路番号 CIRCUIT NO. OF GOLD PLATED CONTACT	色 COLOR
					型番 PART NUMBER

DWN T.MINEMATSU 08APR98		<b>STE</b> TE Connectivity	
CHK E.SASAKI 08APR98			
APVD M.TSUKAKOSHI 08APR98		NAME	
PRODUCT SPEC 108-5603		040III MULTILOCK CONNECTOR 12POSITION CAP HOUSING ASSEMBLY WIRE TO BOARD (H) TYPE	
APPLICATION SPEC		SIZE	RESTRICTED TO
WEIGHT 3.9 g		CAGE CODE A300779	DRAWING NO C-1123413
CUSTOMER DRAWING		SCALE 2:1	SHEET 1 OF 1
			REV D