

	<b>5dB Omni – p/n 2867199</b>	<b>6dB Yagi – p/n 2867209</b>	<b>9dB Yagi – p/n 2867351</b>
<b>Frequency Band</b>	902 to 928 MHz	890 to 960 MHz	890 to 960 MHz
<b>Gain</b>	5dBd / 7.2dBi	6dBd / 8.2dBi	9dBd / 11.2dBi
<b>Type</b>	5/8 over 5/8 over 1/4 wave	4-element (welded)	7-element (welded)
<b>VSWR</b>	1.5:1 or less	1.5:1 or less	1.5:1 or less
<b>Whip</b>	0.100; twin open coil	N/A	N/A
<b>Power Rating</b>	150 W	300 W	300 W
<b>Height</b>	24"	N/A	N/A
<b>Length</b>	N/A	Up to 17"	Up to 31"
<b>Vertical Beam Width</b>	17°	58°	45°
<b>Horizontal Beam Width</b>	N/A	94°	50°
<b>Feed Connection</b>	N(F)	N(F)	N(F)
<b>Wind Load</b>	100 MPH	100 MPH	100 MPH
<b>Mounting</b>	"L" mount bracket; hose clamp fits mast of 3/4" to 1-1/2" diameter	Bracket fits any pipe/pole up to 1-5/8" in diameter	Bracket fits any pipe/pole up to 1-5/8" in diameter