<u>Contact Dimensions:</u>
525-P.C. Tail .018 Sq.(0.46 Sq.) - Tail LG=.150(3.81)
.100 (2.54) Contact Spacing x .200 (5.08) Row Spacing 1 -2x Ø.156[3.96] CARD SLOT ACCEPTS .054" [1.37] TO .070"[1.78] THICK PCB -6.500 [165.1] 6.660 169.16 ·6.975 [177.17 .160[4.06] POINT OF CONTACT CARD SLOT 330 [8.38] .250[6.35] **SECTION A-A** 600 15.24 -7.235[183.77]

- INSULATOR MATERIAL: THERMOPLASTIC PBT BLACK, UL 94V-0
- CONTACT MATERIAL; COPPER TIN ALLOY CONTACT PLATING: GOLD ON THE MATING AREA, TIN PLATING ON THE CONTACT TAILS, NICKEL UNDERPLATE

| 345/395 SERIES CARD EDGE CO | DNNECTOR |
|------------------------------|----------|
| PART NUMBER: 345-064-525-688 | 3 |



| ACAD REFERENCE NO. 345-ENG-MASTER | | | |
|--------------------------------------|---------|-------|--|
| DRAWN: R.STA.MONICA DATE:MAY.16/2017 | | | |
| CHECKED: | DATE: | | |
| SCALE: 1:1 | SHEET 1 | OF 2 | |
| DRAWING NUMBER | | ISSUE | |
| 245 ENIC MARTED | | , , | |

345-ENG-MASTER



.107 [2.72] .082 [2.08] .157 [4] .232 [5.89] .125(3.18) to .210(5.33) .125(3.18) to .210(5.33) Outside Tails Outside Tails .045(1.14) to .060(1.52) .045(1.14) to .060(1.52) Between Tails Between Tails **Contact Code 555 Contact Code 556**







Contact Code 558

Contact Code 559

Contact Code 560

INSULATOR MATERIAL: THERMOPLASTIC POLYESTER, UL 94V-0

DAP MATERIAL AVAILABLE UPON REQUEST

CONTACT MATERIAL; COPPER ALLOY

CONTACT PLATING: GOLD ON THE MATING AREA, TIN PLATING ON THE CONTACT TAILS, NICKEL UNDERPLATE

345/395 SERIES CARD EDGE CONNECTOR CONTACT CODE 555,556,558,559,560 DIMENSIONS

YOUR CONNECTION TO QUALITY & SERVICE

| | ACAD REFERENCE NO | . 345-ENG-MASTER |
|---|---------------------|------------------|
| | DRAWN: R.STA.MONICA | DATE:MAY.16/2017 |
| | CHECKED: | DATE: |
| | SCALE: 1:1 | SHEET 2 OF 2 |
| D | DRAWING NUMBER | ISSUE |

345-ENG-MASTER