





.XX

±0.13 .XXX ±0.05









NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ" GOLD PLATED

POWER/CO-AX CONTACT RATING: (IF PRESENT)


**OPERATING TEMPERATURE:** 

SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX.


INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 10A (CURRENT)

5000MΩ min.

1000V AC rms



SW REFERENCE NO .: 629 COMBO ASSEMBLY COMBINATION D-SUB DATE: JAN. 01/2019 DRAWN: C.B CHECKED: DATE: THESE DRAWINGS AND SPECIFICATIONS OF 2 SCALE: (IN C.A.D. 1:1) SHEET 1 INC ARE THE PROPERTY OF EDAC INC. AND ONTARIO SHALL NOT BE REPRODUCED, OR COPIED 629-3W3-650-1N1 DRAWING NUMBER: ISSUE OR USED AS THE BASIS FOR THE DA MANUFACTURE OR SALE OF APPARATUS 1 SERVICE PART NUMBER: 629-3W3-650-1N1 WITHOUT WRITTEN PERMISSION.



COMPLIANT

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

		EDAC I
		TORONTO, C CANAE
YOUR CO	NNECTION T	O QUALITY & SE

-55°C ~ 125°C

