



TPI111065L210N

Aliases (UPIY111065L21N)

KEMET, TPI, Power, 0.21 uH, 10%, 111065(4539)





Click here for the 3D model.

Dimensions	
L	11.6mm MAX
W	10mm MAX
т	6.5mm MAX
LL	2mm NOM
G	3.5mm +/-0.1mm

Packaging Specifications			
Packaging	T&R, 330mm		
Packaging Quantity	500		

General Information		
Series	TPI	
Style	SMD	
Chip Size	111065(4539)	
Description	Surface Mount Inductor	
Features	DC Optimized TPI Inductors	
RoHS	Yes	
Core	Ferrite	
Miscellaneous	40 (K) Temperature Rise Max.	

0.21 uH
10%
-40/+125°C
Yes
54 A (Isat, 20% Drop In Inductance), 50 A (Irms, 40C Rise By Self Heating)
0.29 mOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.