⊥	m		0			
Z' ØS-						
			LAYOUT SH	OWN AS EXAMPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension	1				
-Standard : Based on MIL-DTL-38999 Series III	DimNominalØS29.4 Max					
-Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	Z' 31.5 Max VV THREAD M18x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer					n & Control List	
-Contact Plating : Gold over copper Alloy 0.8µm minimum				FR No	ot Listed	
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D513M03SEL			
-Temperature Range <u>-</u> -65°C to +200°C						
-Salt Spray : 2000 hours			-2016 First Release			
		ISS DA Designed By:	TE Latest modification - by Date:	CL	JSTOMER DRAWING	MOD N°
		TITLE	TITLE Composite Plug 8D series		eries	
BASIC SERIES: 8D 5 - 13 M 03	S E L	SCALE		ral linear erances:	NPRDS / PROJECT	
SHELL TYPE : Plug with RFI Shielding	Delivered W	/O Contacts NA	$ ((\Psi)) $	±	859 This document is the proper	rty of
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13	ORIE CONTACT TYPE : SOCKET(5	NTATION : E SOURI	AU WWW.SOU	RIAU.COM	SOURIAU it must not be reproduced	lor
PLATING : M = Nickel	CONTACT TYPE : SOCKET(S			JRIAU DRG N°	communicated without perm	SHEET
	CONTACT LAY	A3		513M03SEL-C		1/2

r	Ξ	۵ ا	н т	m	D	0	
		Contact Layout					
4		03					
	Ctc A B C	3#16 13-03 X Y 2.39 1.47 0 -2.79 -2.39 1.47					
ယ							
						SOURIAU shall not be I due to a use of the the Specifications issued (professional re	Products v l by either
N							Cour
						PN: 8	D513
					A 18-10-2	2016 First Release	
					Designed By:	E Latest modification - by Date:	
					SCALE		Comp
_					NA		blerances:
					SOURIA	WWW.SOL	JRIAU.
					FORMAT A3	SO 8C	URIAU 0513M

Н

G

F

Е

	Ξ			A		
						4
						3
ot be liable for any r	non-conformit	ty or dar	nage			
f the Products whic ssued by either of t						
, nal recommendatio			. ,			
Country	Jurisd		Control List			
FR		Not Li	sted			2
I: 8D513M03SEL						
ı - by					MOD N°	
		CUST	OMER DRAWIN	NG		
Composite Plug 8D series						
General linear Tolerances:		NP	RDS / PROJECT			
±	859					1
			his document is the SOURIA it must not be ren	U		
communicated without permi						
SOURIAU DRG N°					SHEET	
8D513M03SEL-C 2/2						
	В			А		

С

D