


C4BSNBX4330ZGMJ

C4BS, Film, Metallized Polypropylene, Power, 3.3 uF, 5%, 600 VAC, 1000 VDC, 70°C, Lead Spacing = 37mm



Click	here	for	the	3D	model.

Dimensions	
L	57.5mm +1.2/-0.7mm
Н	45mm +0.3/-0.7mm
Т	30mm +0.5/-0.7mm
S	37mm +/-0.2mm
S1	4mm +/-0.2mm
Р	25mm NOM

Packaging Specifications				
Packaging	Bulk, Bag			
Packaging Quantity	24			

General Information	
Series	C4BS
Dielectric	Metallized Polypropylene
Style	Radial
Features	IGBT Circuit
RoHS	Yes
Lead	Flat Tabs
AEC-Q200	No
Component Weight	20.6 g
Miscellaneous	KEMET Style G Tabs.

Specifications	
Capacitance	3.3 uF
Capacitance Tolerance	5%
Voltage AC	600 VAC
Voltage DC	1000 VDC
Temperature Range	-40/+85°C
Rated Temperature	70°C
Max dV/dt	512 V/us
Resistance	2.6 mOhms (100kHz)
Ripple Current	34 Amps (100kHz 70C), 1690 Amps (Peak)
Inductance	45 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.