




US32-12-8-F

Ruland US32-12-8-F, 3/4" x 1/2" Single Universal Joint, Friction Bearing, Steel, 1.995" OD, 5.500" Length





Description

Ruland US32-12-8-F is a single cardan friction bearing universal joint with 0.7500" x 0.5000" bores, 1.995" OD, and 5.500" length. It is ideal for applications with space constraints and has higher torque capacity than equivalently sized double universal joints. This plain bearing universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 45° when compared to commodity style single universal joints. US32-12-8-F is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT32/51-NI-KIT to protect the joint from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This single cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

B1 Max Shaft Penetration1.700 inB2 Max Shaft Penetration1.700 inJoint Outer Diameter (OD)1.995 inBore Tolerance+0.0010 in / -0.0000 inLength (L)5.500 inYoke Length (LY)2.750 inLub Depth (LH)1.700 inPeak Torque21,500 in-lbRated Torque4,300 in-lbMax Operating Angle45°Material SpecificationAlloy SteelManufacturerBelden UniversalCountry of OriginUSARecommended LubricantLUBRIPLATE No. 1200-Matching Boot CoverUBOOT32/51-NI-KITUPC63452933347Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular apProp 65MaRNING This product can expose you to the chemical Ethylene Thiourea, known to the Stat California to cause cancer and birth defects or other reproductive harm. For more information go	Frouuci opecifications			
Joint Outer Diameter (OD)1.995 inBore Tolerance+0.0010 in / -0.0000 inLength (L)5.500 inYoke Length (LY)2.750 inHub Depth (LH)1.700 inPeak Torque21,500 in-lbRated Torque4,300 in-lbMax Operating Angle45°Material SpecificationAlloy SteelManufacturerBelden UniversalCountry of OriginUSARecommended LubricantLUBRIPLATE No. 1200-Matching Boot CoverUBOOT32/51-NI-KITUPC63452933347Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular apProp 65▲WARNING This product can expose you to the chemical Ethylene Thiourea, known to the Star California to cause cancer and birth defects or other reproductive harm. For more information go	Bore (B1)	0.7500 in	Small Bore (B2)	0.5000 in
Length (L)5.500 inYoke Length (LY)2.750 inHub Depth (LH)1.700 inPeak Torque21,500 in-lbRated Torque4,300 in-lbMax Operating Angle45°Material SpecificationAlloy SteelManufacturerBelden UniversalCountry of OriginUSARecommended LubricantLUBRIPLATE No. 1200Matching Boot CoverUBOOT32/51-NI-KITUPC63452933347Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular approp 65AWARNING This product can expose you to the chemical Ethylene Thiourea, known to the Star California to cause cancer and birth defects or other reproductive harm. For more information go	B1 Max Shaft Penetration	1.700 in	B2 Max Shaft Penetration	1.700 in
Hub Depth (LH)1.700 inPeak Torque21,500 in-lbRated Torque4,300 in-lbMax Operating Angle45°Material SpecificationAlloy SteelManufacturerBelden UniversalCountry of OriginUSARecommended LubricantLUBRIPLATE No. 1200-Matching Boot CoverUBOOT32/51-NI-KITUPC63452933347Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular apperProp 65MWARNING This product can expose you to the chemical Ethylene Thiourea, known to the State California to cause cancer and birth defects or other reproductive harm. For more information go	Joint Outer Diameter (OD)	1.995 in	Bore Tolerance	+0.0010 in / -0.0000 in
Rated Torque4,300 in-lbMax Operating Angle45°Material SpecificationAlloy SteelManufacturerBelden UniversalCountry of OriginUSARecommended LubricantLUBRIPLATE No. 1200-Matching Boot CoverUBOOT32/51-NI-KITUPC63452933347Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular approp 65Marking This product can expose you to the chemical Ethylene Thiourea, known to the State California to cause cancer and birth defects or other reproductive harm. For more information go	Length (L)	5.500 in	Yoke Length (LY)	2.750 in
Material Specification Alloy Steel Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 1200- Matching Boot Cover UBOOT32/51-NI-KIT UPC 63452933347 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular approp 65 California to cause cancer and birth defects or other reproductive harm. For more information go	Hub Depth (LH)	1.700 in	Peak Torque	21,500 in-lb
Country of OriginUSARecommended LubricantLUBRIPLATE No. 1200Matching Boot CoverUBOOT32/51-NI-KITUPC63452933347Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular apProp 65MWARNING This product can expose you to the chemical Ethylene Thiourea, known to the State California to cause cancer and birth defects or other reproductive harm. For more information go	Rated Torque	4,300 in-lb	Max Operating Angle	45°
Matching Boot Cover UBOOT32/51-NI-KIT UPC 63452933347 Fraiff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular ap Prop 65 Marking This product can expose you to the chemical Ethylene Thiourea, known to the State California to cause cancer and birth defects or other reproductive harm. For more information go	Material Specification	Alloy Steel	Manufacturer	Belden Universal
Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular approp 65Prop 65MARNING This product can expose you to the chemical Ethylene Thiourea, known to the State California to cause cancer and birth defects or other reproductive harm. For more information go	Country of Origin	USA	Recommended Lubricant	LUBRIPLATE No. 1200-2
Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular approp 65 California to cause cancer and birth defects or other reproductive harm. For more information go	Matching Boot Cover	UBOOT32/51-NI-KIT	UPC	63452933347
Prop 65 AWARNING This product can expose you to the chemical Ethylene Thiourea, known to the Stat California to cause cancer and birth defects or other reproductive harm. For more information go	Tariff Code	8483.60.4000	UNSPC	25173810
California to cause cancer and birth defects or other reproductive harm. For more information go	Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
	Prop 65	WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov .		