

T1 Shielded RJ48C Patch Cable (RJ45 M/M), 3-ft., TAA

MODEL NUMBER: N265-003



Highlights

- 22AWG, 100ohm T1 Rated Cable
- Connects your T1 CSU/DSU
- Meets ANSI T1.403 Cabling Requirement
- Compliant with the Federal
 Trade Agreements Act (TAA) for
 GSA Schedule purchases

Package Includes
3ft T1 Shielded RJ48C Patch
Cable

Description

Tripp Lite's T1, RJ45-RJ45, (RJ48C) Patch Cables are constructed with premium Quabbin 9720, T1 certified cable. Two individually shielded, 22AWG, 100ohm pairs, maximize the performance of your expensive T1 circuits and equipment. Beware of generic T1 patch cables made with inexpensive Cat5 unshielded patch cable. The American National Standards Institute (ANSI) states in ANSI T1.403 that T1 cable be constructed of two balanced pairs, 22 AWG Solid conductor, 100ohm impedance, with a loss budget of 5.5db. Straight through wiring configuration available in 3ft, 5ft, 7ft, and 10ft lengths. Custom lengths available...consult your reseller. Also available in Crossover wiring configuration...see Tripp Lite N266- Series T1 patch cables.

Features

- ANSI certified T1 cable, Levels 1, 1A, and 1C
- Complies with ANSI T1.403 Carrier-to-Customer Installation-DS1 Metallic Interface
- Straight through T1 wiring configuration
- Available in 3ft, 5ft, 7ft, and 10ft stocked lengths
- Custom length cables available
- NEC (UL) Type CMR
- Available in Crossover wiring configurations
- 22AWG Solid Tinned Copper

Specifications

OVERVIEW	
UPC Code	037332150301
INPUT	





Cable Length (ft.)	3	
Cable Length (m)	0.9	
Cable Length (in.)	36	
Cable Length (cm)	91.4	
PHYSICAL		
Cable Jacket Rating	CMR	
Color	Beige	
Shipping Dimensions (hwd / cm)	0.25 x 19.30 x 21.84	
Shipping Dimensions (hwd / in.)	0.10 x 7.60 x 8.60	
Shipping Weight (kg)	0.05	
Shipping Weight (lbs.)	0.10	
Snagless Connector	No	
Wire Gauge (AWG)	22	
Wire Type	Solid	
CONNECTIONS		
Side A - Connector 1	RJ45 (MALE)	
Side B - Connector 1	RJ45 (MALE)	
FEATURES & SPECIFICATIONS		
Technology	T1	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies