


R523I4100JBP0M

Aliases (523I4100JBP0M)

R52 310 VAC MINI, Film, Metallized Polypropylene, Automotive Safety, 1 uF, 20%, 310 VAC (X2), 630 VDC, 110 °C, Lead Spacing = 15mm



Click here for the 3D model.

Dimensions	,
L	18mm +0.3/-0.5mm
Н	20mm +0.1/-0.5mm
Т	12mm +0.2/-0.5mm
S	15mm +/-0.4mm
LL	3.5mm +0.5mm
F	0.8mm +/-0.05mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	400

General Information			
Series	R52 310 VAC MINI		
Dielectric	Metallized Polypropylene		
Style	Radial		
Features	EMI Safety		
RoHS	Yes		
Lead	Wire Leads		
Safety Class	X2		
Qualifications	ENEC, UL, cUL, CQC, AEC-Q200		
AEC-Q200	Yes		
THB Performance	Yes		
Component Weight	6.1 g		

Specifications	
Capacitance	1uF
Capacitance Tolerance	20%
Voltage AC	310 VAC (X2)
Voltage DC	630 VDC
Temperature Range	-40/+110°C
Rated Temperature	110°C
Dissipation Factor	0.2% 1kHz
Insulation Resistance	30 GOhms
Max dV/dt	400 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.