

Cable marker - LS-WMTB-V4A (100X15) - 0831519

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Cable marker, Stainless steel label, silver, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, mounting type: Assembly with cable binders, cable diameter: > 4.6 mm, lettering field size: 100 x 15 mm, Number of individual labels: 8




Your advantages

- Stainless steel cable marking for assembly with cable binders
- High-quality appearance
- Suitable for large-surface marking of conductors and cables > 4.6 mm in diameter



Key Commercial Data

Packing unit	5 pc
Minimum order quantity	5 pc
GTIN	 4 046356 925297
GTIN	4046356925297

Technical data

Dimensions

Length (b)	118 mm
Width (a)	15 mm
Material thickness (g)	0.50 mm

Ambient conditions

Ambient temperature (operation)	-80 °C ... 400 °C
---------------------------------	-------------------

General

Color	silver
Type	Card form
Components	free from silicone, halogen, and cadmium
Material	V4A
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)

Cable marker - LS-WMTB-V4A (100X15) - 0831519

Technical data

General

Number of individual labels	8
Marking mounting type	Assembly with cable binders

Classifications

eCl@ss

eCl@ss 10.0.1	27400401
eCl@ss 11.0	27281102
eCl@ss 4.0	27061700
eCl@ss 4.1	27061700
eCl@ss 5.0	27400400
eCl@ss 5.1	27400400
eCl@ss 6.0	27400400
eCl@ss 7.0	27400401
eCl@ss 9.0	27400401

ETIM

ETIM 4.0	EC001530
ETIM 6.0	EC001530
ETIM 7.0	EC001530

UNSPSC

UNSPSC 13.2	39131504
UNSPSC 18.0	39131504
UNSPSC 19.0	39131504
UNSPSC 20.0	39131504
UNSPSC 21.0	39131504

Accessories

Accessories

Cable tie

Cable tie - WT-STEEL SH 4,6X150 - 3240820



Cable binders, made from rust-free stainless steel (AISI 316), suitable for the harshest of ambient conditions (for example, salt water), with ball lock, for quick and secure bundling and fastening

Cable marker - LS-WMTB-V4A (100X15) - 0831519

Accessories

Cable tie - WT-STEEL S 4,6X150 - 3240807



Cable binders, made from rust-free stainless steel (AISI 304), suitable for harsh ambient conditions, with ball lock, for quick and secure bundling and fastening

Cable tie - WT-HF 4,5X160 BK - 3240757



Cable binders for quick and secure bundling, standard version

Cable tie - WT-UV HF 4,5X200 BK - 3240834



Cable binders for quick and permanent fastening, UV-resistant and weatherproof (ISO 4892_QUV-B 600 h)

Cable tie - WT-HT HF 4,5X200 BK - 3240787



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

Cable tie - WT-HT HF 4,5X200 - 3240786



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

Cable marker - LS-WMTB-V4A (100X15) - 0831519

Accessories

Cable tie - WT-HP HF 4,5X290 - 0830984



Cable binders for quick and secure bundling, standard version

Cable tie - WT-ID HF 4,5X200 BU - 3240797



Cable binders for quick and secure fastening, can be detected using metallic pigments

Cable tie - WT-HF 4,5X160 - 3240756



Cable binders for quick and secure bundling, standard version

Magazine

Magazine - TOPMARK LASER-MAG SHEET - 0831836



Sheet magazine for TOPMARK LASER

Printing system

Laser marker - TOPMARK NEO SET - 1012018



Laser marker incl. extraction unit with operating instructions, declaration of conformity, LS adapter plate +4 magnets, LS retaining plate, power cables: type E and F, LAN cable, D-SUB cable 25-pos., suction tube, crevice nozzle set and filter equipment

Printing system accessories

Cable marker - LS-WMTB-V4A (100X15) - 0831519

Accessories

Adapter plate - TMN-ADAPTER PLATE-LS - 1012104



Adapter plate, for LS materials, for TOPMARK NEO, weight: 0.193 kg

Phoenix Contact 2021 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>