

## Han F+B Hybrid Male



Image is for illustration purposes only. Please refer to product description.

Part number	09 15 512 3001
Specification	Han F+B Hybrid Male
HARTING eCatalogue	<a href="https://b2b.harting.com/09155123001">https://b2b.harting.com/09155123001</a>

### Identification

Category	Inserts
Series	Han <sup>®</sup> F+B

### Version

Termination method	Crimp termination
Gender	Male
Number of contacts	12
Number of data contacts	4
Number of signal contacts	4
Number of power contacts	4
PE contact	Yes
Details	Please order crimp contacts separately. 4x Han E <sup>®</sup> 4x Han D <sup>®</sup> 4x M12 for data element

### Technical characteristics

Conductor cross-section	0.14 ... 4 mm <sup>2</sup>
Rated current (signal)	10 A
Rated voltage (signal)	250 V
Rated impulse voltage (signal)	4 kV
Pollution degree (signal)	3
Rated current (power)	20 A
Rated voltage (power)	400 V



Pushing Performance

## Technical characteristics

Rated impulse voltage (power)	6 kV
Pollution degree (power)	3
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s
Insulation resistance	$>10^{10} \Omega$
Limiting temperature	-40 ... +125 °C
Mating cycles	$\geq 500$
Mating cycles with other HMC components	$\geq 3,000$

## Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0

## Commercial data

Packaging size	1
Net weight	15.75 g
Country of origin	Germany
European customs tariff number	85389099
eCI@ss	27440205 Contact insert for industrial connectors