


USEQMSM1220900

Aliases (USEQMSM1220900)

KEMET, QMSM, Motion Detection, SMD, Infrared, Small SMD Package, 12C Communication Compatible, High Dynamic Range



Dimensions	
L	13.8mm NOM
L2	10mm NOM
Н	16mm NOM

Packaging Specifications			
Packaging	Bulk		
Component Weight	5.4 g		

General Information		
Series	QMSM	
Туре	Motion Detection	
Style	SMD	
Description	12C Motion Sensor Module	
Features	Small SMD Package, 12C Communication Compatible, High Dynamic Range	
RoHS	With Exemptions	
REACH	SVHC (PZT – CAS 12626-81-2)	
SCIP Number	4bbe8810-62a4-426f-9a2e-98d9d0d9acfe	
Qualifications	REACH	
MSL	3	

Specifications		
Temperature Range	-40/+85°C	
Power Supply Voltage	1.75 - 3.6 V	
Current	1 - 23 uA (Supply Current, Typical)	
Miscellaneous	Includes sensor: USEQMSEA220980.	
D*	5.5 x 10^8 cm sqrt(Hz)/ W	
NEP	0.4 x 10^-10 W/sqrt(Hz)	
Time Constant	10ms (10-20 Hz peak)	
Field of View	60 degrees	
Element Size	0.057 mm x 0.057mm (4 pixels)	
Filter Aperture	d = 0.9 mm	
Filter	5.0 um Long Pass	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.