

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0348992071](#)

Status: **Active**

Overview:

Description: MXP120 Sealed Male Blade Connector with 7.00mm Clip-Slot, 2 Circuit, Yellow SIR Housing (T3-V2-S2 - 125°C on-engine vibration), Wire Dress Cover Interface Option 2, Key B

Application tooling part link

Application Tooling Part Link 63824-6300

General

Product Family Crimp Housings
Series [34899](#)
Application Automotive, Safety, Sealed, Wire-to-Wire
Comments See sales drawing for terminal information.
Overview 120mm_sealed_connection_system_
Polarization B
Product Name MXP120 Sealed
UPC 889056517812

Physical

Circuits (maximum) 2
Color - Resin Yellow
Gender Plug
Glow-Wire Capable No
Keying to Mating Part Yes
Lock to Mating Part Yes
Material - Resin SPS/Nylon
Net Weight 3.500/g
Number of Rows 1
Packaging Type Bag
Panel Mount No
Pitch - Mating Interface 4.00mm
Pitch - Termination Interface 4.00mm
Polarized to Mating Part Yes
Temperature Range - Operating -40° to +125°C

Electrical

Current - Maximum per Contact 13.0A

Material Info

Reference - Drawing Numbers

Application Specification AS-34900-0001-001
Packaging Specification PK-31301-898-001
Sales Drawing SD-34899-2001-001, SD-34899-6001-001

**EU ELV
Compliant**

**EU RoHS
Compliant**

China RoHS

REACH SVHC

Not Contained Per -
D(2021)4569-DC (8
July 2021)

Halogen-Free

Status

Not Relevant

For more information, please visit [Contact US](#)

China ROHS

Not Relevant

ELV

Compliant

RoHS Phthalates

Not Contained

Search Parts in this Series

[34899](#) Series

Mates With

MXP120 Female Receptacle [34900](#)

Use With

Tyco 1.2 MCON terminals
Or
Kostal
MLK 1.2 terminals

Application Tooling | [FAQ](#)

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description

Product #

Extraction Toolkit [638246300](#)
for MXP120 Sealed
Connection System