

Interface module - UMKS- C64M-VS - 2970565


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE module, for IEC 603/DIN 41612 connector, type C, 64-pos., a, c components mounted, with male connector, cable housing with screw interlock



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 pc |
| GTIN |  4 017918 087753 |
| GTIN | 4017918087753 |

Technical data

Dimensions

| | |
|--------|--------|
| Width | 135 mm |
| Height | 77 mm |
| Depth | 72 mm |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Degree of protection | IP20 |

General

| | |
|---------------------------------|-------------|
| Nominal voltage U_N | 125 V AC/DC |
| Max. perm. current (per branch) | 1 A |
| Number of positions | 64 |
| Mounting position | any |
| Degree of protection | IP20 |

Connection data

| | |
|----------------------------------|-------------|
| Connection name | Field level |
| Connection in acc. with standard | IEC / EN |

Interface module - UMKS- C64M-VS - 2970565

Technical data

Connection data

| | |
|----------------------------------|---|
| Connection method | Screw connection |
| Stripping length | 8 mm |
| Screw thread | M3 |
| Conductor cross section solid | 0.2 mm ² ... 4 mm ² |
| Conductor cross section flexible | 0.2 mm ² ... 2.5 mm ² |
| Conductor cross section AWG | 24 ... 12 |

Connection data 2

| | |
|---------------------|------------------------------|
| Connection name | Controller level |
| Connection method | IEC 603/DIN 41612 connection |
| Number of positions | 64 |

Standards and Regulations

| | |
|--------------------------|--------------------------------|
| Standards/regulations | DIN EN 50178 |
| | IEC 60664 |
| Rated insulation voltage | 125 V |
| Rated surge voltage | 1.2 kV (Functional insulation) |
| Degree of pollution | 2 |
| Overvoltage category | II |

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|---|--------------------------|
| EAC |  | RU C- DE.A*30.B.01742 |
|-----|---|--------------------------|

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>