

## R60DF4330JH6AJ

Aliases (60DF4330JH6AJ)

R60, Film, Metallized Polyester Stacked, Automotive Grade, 3.3 uF, 5%, 63 VDC, 85°C, Lead Spacing = 10mm



Click [here](#) for the 3D model.

### Dimensions

|    |                   |
|----|-------------------|
| L  | 13mm +0.2mm       |
| H  | 12mm +0.1mm       |
| T  | 6mm +0.2mm        |
| S  | 10mm +/-0.4mm     |
| LL | 3.2mm +0.3/-0.2mm |
| F  | 0.6mm +/-0.05mm   |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 1000      |

### General Information

|                |   |
|----------------|---|
| Series         | R60   |
| Dielectric     | Metallized Polyester Stacked  |
| Style          | Radial  |
| Features       | Automotive Grade, DC Multipurpose Applications  |
| RoHS           | Yes   |
| Lead           | Cut   |
| Qualifications | AEC-Q200  |
| AEC-Q200       | Yes   |
| Miscellaneous  | Upper Operating Temperature Of 125C Is Allowed For A Maximum Operating Time Of 1,000 Hours. Above 85C, DC And AC Voltage Derating Is 1.25%/C. |

### Specifications

|                       |             |
|-----------------------|-------------|
| Capacitance           | 3.3 uF      |
| Capacitance Tolerance | 5%          |
| Voltage AC            | 40 VAC      |
| Voltage DC            | 63 VDC      |
| Temperature Range     | -55/+105°C  |
| Rated Temperature     | 85°C        |
| Dissipation Factor    | 1% 1kHz     |
| Insulation Resistance | 378.8 MOhms |
| Max dV/dt             | 50 V/us     |
| Inductance            | 9 nH        |