



Crimping tool for crimping wire-end ferrules with and without plastic collars. Cross-section range: 0.5-6 mm² (AWG 2-10). Easy to use, Auto-lock for proper and complete crimping, Wires fed in from the front, Self-opening with built-in spring.

Business data

Article number	1100.0
Article name	PZU 6
GTIN (EAN)	4044211016357
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	500 g
Weight per piece (including packaging)	576 g
Unit of weight	G
Customs number	82032000
Country of origin	DE
Product description	Crimping tool

Technical data

Dimensions

Length	210 mm
--------	--------

Application

Crimp shape	Trapezoidal crimp
-------------	-------------------

Crimping range, min.	0.14 mm ²
----------------------	----------------------

Crimping range, max.	6 mm ²
----------------------	-------------------

Crimping range AWG, min.	26
--------------------------	----

Crimping range AWG, max.	10
--------------------------	----

Wire-end ferrule cross-section, min.	0.5 mm ²
--------------------------------------	---------------------

Max wire-end ferrule cross-section	6 mm ²
------------------------------------	-------------------

Environmental Product Compliance

REACH Conform	yes
---------------	-----

REACH Reference date	2022-06-10
----------------------	------------

REACH Candidate Substance Note	No
--------------------------------	----

RoHS Conform	yes
--------------	-----

Media

Accessories
