

## Patch panels - FL PF 2TX CAT 6 - 2891068

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Patch field with two RJ45 CAT6 network connections

### Your advantages

- ✓ Flexibility through the replacement of patch elements with fiber optic patch elements - Future proof through standardized installation according to CAT5 and CAT6
- ✓ Future proof through standardized installation according to CAT5 and CAT6
- ✓ Security through extension with FL PLUG GUARD



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 084383
GTIN	4046356084383

### Technical data

#### Dimensions

Width	38 mm
Height	112 mm
Depth	88 mm

#### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 55 °C (non-condensing)
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)

#### Interfaces

Interface	Ethernet (RJ45)
No. of ports	2

## Patch panels - FL PF 2TX CAT 6 - 2891068

### Technical data

#### Conformity with EMC directives

Developed in acc. with standard	ISO/IEC 11801, EN 50173, TIA/EIA 568B and IEC 60603-7
---------------------------------	---

#### General

Net weight	120.2 g
Housing material	Metal

#### Connection data

Conductor cross section	0.2 mm <sup>2</sup> ... 0.32 mm <sup>2</sup>
Connection cross section AWG	24 ... 22
Rated voltage (III/3)	50 V
Rated surge voltage	≥ 1 kV
Rated current	1 A

---

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>