



General Information		
Series	ACA Indust COG HT200C	
RoHS	No	
Prop 65	WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
SCIP Number	a54cd522-25fb-4dac-afe5-a404d68708e3	
Termination	Gold	
Failure Rate	N/A	
AEC-Q200	No	
Notes	Lead Length Shown Is For Parts Supplied In Bulk, See Packaging Specifications For Lead Lengths When Not Provided In Bulk.	

Specifications		
Capacitance	3900 pF	
Capacitance Tolerance	10%	
Voltage DC	50 VDC	
Dielectric Withstanding Voltage	125 VDC	
Temperature Range	-55/+200°C	
Temperature Coefficient	COG	
Dissipation Factor	0.15% 1 kHz 1.0Vrms	
Insulation Resistance	100 GOhms	

Click here for the 3D model.

Dimensions	
L	10.16mm MAX
W	3.81mm MAX
Т	3.81mm MAX
LL	3.175mm MIN
F	0.635mm +/-0.051mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	1

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.