





| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 43.8              |
| B   | 1 1/2-18NEF-2B    |
| C   | 1 7/16-18NEF-2A   |
| D   | 66                |
| E   | 27.5              |
| F   | 32                |
| G   | 9.4               |

| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 2   | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3   | DICHTKÖRPER / GROMMET                   |
| 4   | ENDRING / ENDRING                       |
| 6   | KONTAKTBUCHSE / CONTACT SOCKET          |
| 7   | ZYLINDERGHÄUSE / BARREL                 |
| 9   | ÜBERWURFMUTTER / COUPLING NUT           |
| 10  | DICHRING FRONT / FRONT SEALING RING     |
| 14  | F-ENDGEHÄUSE / F-ENDBELL                |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

Material Specification:  
 Shell Material: Aluminium alloy  
 Shell Plating: Olive drab chromate coating over cadmium plating  
 Insulator Material: Neoprene  
 Contact Material: Copper alloy  
 Contact Plating: Hard silver

|   |   |                            |
|---|---|----------------------------|
| all dimensions are in mm<br>Dimensions without tolerance indications are general tolerances in acc. with DIN7168m   |   | drawing for<br>CUSTOMER    |
| <br><b>ITT</b><br><i>Engineered for life</i><br><small>ITT CANNON GmbH<br/>D - 71384 Weinstadt/Germany</small> | description   | CA3108F24-20S-F80          |
|   | Plug 90°<br>Endbell for flex tube<br>AWG Crimp / Socket / Layout: 24-20 |                            |
| © All rights reserved. Reproduction or issue to third in any form whatever is only permitted with written authorization of ITT Cannon   | page<br>1/1   | revision<br>929 11. Jun 19 |