



All dimensions are in mm; tolerances according to ISO 2768 c

**Preliminary**

<i>cable</i>	<i>cable type</i>	<i>cavity side A</i>	<i>cavity side B</i>
A3	Dacar 462	1	4
A4	Dacar 462	2	3
A5	Dacar 462	3	2
A6	Dacar 462	4	1

cable length		
range of length "Ax" (mm)	≤ 300	> 300
tolerance for "Ax"	± 3 mm	± 1 %

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/09\_14/6.2

**Interface**

According to RN\_108-01

**Documents**

Technical data sheet connector AMK12A-102Z5  
 Technical data sheet housing AMZ025-000

**Environmental data**

Temperature range -40°C to +105°C  
 RoHS compliant

**Preliminary**

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
J. Lamprecht	16.03.18	J. Lamprecht	26.03.18	200	18-v202	T. Unterhauser	26.03.18

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>				Tel. : +49 8684 18-0 Email : <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>			Page 2 / 2
--	--	--	--	--	--	--	---------------