



NOTE:

1. ELECTRICAL CHARACTERISTICS
 - 1-1 RATING CURRENT: 2A AC/DC
 - 1-2 RATING VOLTAGE: 250V AC/DC
 - 1-3 WITHSTANDING VOLTAGE: 800V AC/1MINUTE
 - 1-4 OPERATING TEMPERATURE: -40°C~+105°C
 2. MATERIAL: REFER TO ORDERING CODE
 3. FINISH: BRIGHT TIN PLATING
 4. INSULATION O.D.: $\phi 1.30\text{MM MAX}$
WIRE SIZE: AWG#24~26 (0.22~0.13mm²)
 5. USED WITH AFCI 10156614
 6. PRODUCT SPEC: GS-12-1594
 7. ORDERING CODE: 10156615-X 0 0 X LF
- MATERIAL: +-BRASS
2: PHOSPHOR BRONZE
- PACKAGE: 1: REEL

SECTION: A-A
SCALE: 1:1

SECTION: B-B
SCALE: 1:1

SECTION: C-C
SCALE: 1:1

mat'l. code	surf'ce	tolerance	projection	product family
A	New release	ISO 1302	110°	MINITEK
B	ECN no.	ISO 406	110°	
	dr	ISO	mm	
	date	tolerances unless otherwise specified	scale 2:1	
	2020-2-19	.X±.3		
	Jason	.XX±.20		
	2020-4-2	.XXX±.10		
	0±x'			
	dr	Jason Wang	2020-1-19	
	engr	Jason Wang	2020-4-2	
	chr	-	-	
	qppd	Tim Yao	2020-4-2	
sheet	revision	B		
index	sheet	1		
	dwg no	sheet 1 of 1	size	
	10156615	A3		
	type	Product Customer Drawing		

product family
MINITEK

title
2.0PITCH BOARD-IN, Vertical , TERMINAL