


THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.






10.70

Ν	0	ΓE	S:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED
OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	30A (CURRENT)
SIGNAL CONTACT CURRENT RATING SIGNAL CONTACT RESISTANCE:	: 5A PER CONTACT 10mΩ MAX.
INSULATOR RESISTANCE:	5000MΩ min.
DIELECTRIC WITHSTANDING VOLTAGE:	1000V AC rms

	SW REFERENCE NO.: 630 COMBO ASSEMBLY			
COMBINATION	DRAWN: C.B	DATE: JAN. 01/201	9	
	CHECKED:	DATE:		
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE	DRAWING NUMBER: 630-3W3	-250-3N3	ISSUE
YOUR CONNECTION TO QUALITY & SERVICE MANUFACTURE OR SALE OF APPARAT WITHOUT WRITTEN PERMISSION.		PART NUMBER: 630-3W3	-250-3N3	1



ĦS

COMPLIANT

Г

