ATGBICS FTLF1519P1WNL Finisar Compatible Transceiver SFP 2GBase-ZX (1550nm, SMF, 80km, LC, DOM, Ext Temp)

Brand: ATGBICS Product code: FTLF1519P1WNL-C

Product name: FTLF1519P1WNL Finisar Compatible Transceiver SFP 2GBase-ZX (1550nm, SMF, 80km, LC, DOM,

Ext Temp)

FTLF1519P1WNL Finisar Compatible Transceiver SFP 2GBase-ZX (1550nm, SMF, 80km, LC, DOM, Ext

ATGBICS FTLF1519P1WNL Finisar Compatible Transceiver SFP 2GBase-ZX (1550nm, SMF, 80km, LC, DOM, Ext Temp):

ATGBICS FTLF1519P1WNL 2GBase-ZX supports a distance of up to 80km over single mode fibre (SMF) using a wavelength of 1550nm via an LC connector. This product can operate at extended temperatures between -5 to 85°C. Digital optical monitoring (DOM) support is also present enabling realtime monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Finisar FTLF1519P1WNL= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Power	
SFP transceiver type * Fiber optic Maximum data transfer rate * 2125 Mbit/s Interface type * SFP	2125 Mbit/s SFP	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 0.8 W
Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported	×	Operational conditions	F 00
Fiber optic connector SFP transceiver standard Maximum transfer distance Wavelength Ethernet LAN Ethernet interface type	LC ZX 80000 m 1550 nm 2.5 Gigabit Ethernet	Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-5 °C 85 °C -5 - 85 °C -40 - 85 °C 0 - 85% 5 - 95%
Digital Diagnostics Monitoring		Weight & dimensions	
(DDM) Wavelength-division multiplexing (WDM)	×	Width Depth Height	13.4 mm 56.5 mm 8.5 mm
Features		Weight	15 g
roduct colour Silver ousing material Metal ug and Play ot-Plug support		Packaging data Number of products included Package type	1 pc(s) Box
Hot-swap	4	Technical details	
Easy to install Country of origin Brand compatibility Certification	China Finisar CE, FCC, RoHS	Sustainability compliance Sustainability certificates Doesn't contain	RoHS Lead



5056468768292

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.