

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of GRM032D80G105ME01# from the official website of Murata Manufacturing Co., Ltd.

"#" indicates a package specification code.

http://www.murata.com/en-us/products/productdetail?partno=GRM032D80G105ME01%23

GRM032D80G105ME01D




< List of part numbers with package codes > GRM032D80G105ME01D GRM032D80G105ME01J

Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Mobile Electronics
	Please refer to Our Website and
	specifications, etc. for information about
Specific	the performance, functions, quality,
Applications	management, and safety required for
Applications	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.

Appearance & Shape





Notices

Derating1. Only for mobile devices



References

Packaging	Specifications	Standard Packing Quantity
D	φ180mm Reel Paper Tape	15000
J	φ330mm Reel Paper Tape	50000

Mass (typ.)	
1 piece	0.2mg

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GRM032D80G105ME01D

Note: This datasheet may be out of date. Please download the latest datasheet of GRM032D80G105ME01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GRM032D80G105ME01%23

"#" indicates a package specification code.



Specifications

Length	0.6±0.09mm
Width	0.3±0.09mm
Thickness	0.2±0.02mm
Capacitance	1.0µF ±20%
Distance between external terminals g	0.2mm min.
External terminal size e	0.1 to 0.2mm
Operating Temperature Range	-55℃ to 105℃
Rated Voltage	4Vdc
Size code in inch(mm)	0201 (0603M)
Capacitance change rate	+22.0/-33.0%
Temperature characteristics (complied standard)	X6T(EIA)
Temperature range of temperature characteristics	-55℃ to 105℃

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

