ASSOCIATION CONNECTING LECTRONICS INDUSTRIES® INDUSTRIES®	PC. Bannockl	ourn. Illinois. A	Ill rights reserved untions.	under both	This docum level parts, t	ent is a declara the declaration	tion of the s encompass	substances es all lowe	within the er level mat	manufacture rerials for wh	er listed it hich the m	em. Note: anufacture	if the item is an a er has engineering	ssembly with lower responsibility.	
				Form Type Distribute	*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materia					als and M	als and Mfg Information			
Supplier Information															
Company name*			Company unique ID			Unique ID Authority					Response Date*				
onsemi											2023-06-08				
Contact Name Title - Contact			;t			Phone - Contact*				Email - Contact*					
Product-Env-Stewards Pro			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com					
Authorized Representative* Tit			Title - Representative			Phone - Representative*				Email - Representative*					
Product-Env-Stewards Pro			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com					
Requester Item Number	er Mfr Item Num		Number Mfr Item Name			Effective Da	e Version	on Manufacturing Site		ring Site	1	Weight*	UOM	Unit Type	
	MM74H	MM74HC240SJX INVERTING		OCTAL 3-ST BUFF		2023-06-08			PH4		2	284.052	mg	Each	
Manufacturing Proccess Informa	tion														
Terminal Plating / Grid Array M	Terminal Plating / Grid Array Material Terminal Base Alloy			J-STD-020 MSL	MSL Rating Peak Process Body Temperature Max Time at Peak					ime at Peak '	Temperature Number of Reflow Cycles				
Matte Tin (Sn) - annealed CU Alloy			1		260		С	30		secon	ds 3				
Comments															
level 1 - maximum time at peak temperat	ire during so	Idering is 10-3	0 seconds												
For more information regarding material	composition	please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth					
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted					
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all				
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.									
Supplier Digital Signature Ra	stislav Drska	Le							

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	1.65	mg	Supplier	Silicon (Si)	7440-21-3		1.65	mg	
Die Attach	0.812	mg	Supplier	Silver (Ag)	7440-22-4		0.6374	mg	
			Supplier	Phenolic Resin-2	54208-63-8		0.1746	mg	
Lead Frame	84.2	mg	Supplier	Zinc (Zn)	7440-66-6		0.109	mg	
			Supplier	Iron (Fe)	7439-89-6		2.0208	mg	
			Supplier	Copper (Cu)	7440-50-8		82.0363	mg	
			Supplier	Phosphorus (P)	7723-14-0		0.0339	mg	
Mold Compound-Black	194.0	mg	Supplier	2,6-dibromo-4-[1-(3-bromo-4- hydroxyphenyl)-1-methylethyl]phenol	6386-73-8		1.94	mg	
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		55.29	mg	
			В	Antimony Trioxide (Sb2O3)	1309-64-4		5.82	mg	
			Supplier	Carbon Black (C)	1333-86-4		1.94	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		129.01	mg	
Plating	2.85	mg	Supplier	Tin (Sn)	7440-31-5		2.85	mg	
Wire Bond - Au	0.54	mg	Supplier	Gold (Au)	7440-57-5		0.54	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signar range of distribution unless otherwise noted)