


NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ" GOLD PLATED



POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX. **INSULATOR RESISTANCE:** 5000MΩ min. DIELECTRIC

.XX ±0.13 .XXX ±0.05


WITHSTANDING VOLTAGE:

OPERATING TEMPERATURE:

40A (CURRENT)

-55°C ~ 125°C

1000V AC rms



| | | | SW REFERENCE NO.: 629 COMBO ASSEMBLY | | |
|-------------|--------------------------------------|---|--------------------------------------|-------------------------------|-------|
| | COMBINATION | D-SUB | DRAWN: C.B | DATE: JAN. 01/20 ⁻ | 19 |
| | | | CHECKED: DATE: | | |
| то | EDAC INC | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND | SCALE: (IN C.A.D. 1:1) | SHEET 1 OF | 2 |
| VES NCY. | YOUR CONNECTION TO QUALITY & SERVICE | SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | DRAWING NUMBER: 629-25W3650-4N1 | | ISSUE |
| | | | PART NUMBER: 629-25W | 3650-4N1 | 1 |



THIS SERIES FULLY CONFORMS T THE EUROPEAN UNION DIRECTIVE 2011/65/EU FOR RoHS COMPLIANC

