




.XX ±0.13

.XXX ±0.05











## NOTES:

| MATERIAL:<br>HOUSING:<br>SHELL:<br>CONTACT:                  | THERMOPLASTIC POLYESTER, UL94V-0<br>STEEL, NICKEL PLATED<br>COPPER ALLOY, GOLD FLASH PLATED |
|--|---|
| OPERATING TEMPERATURE:                                       | -55°C ~ 125°C   |
| POWER/CO-AX CONTACT RATING:<br>(IF PRESENT)                  | 30A (CURRENT)   |
| SIGNAL CONTACT CURRENT RATING:<br>SIGNAL CONTACT RESISTANCE: | 5A PER CONTACT<br>10mΩ MAX.   |
| SIGNAL CUNTACT RESISTANCE:                                   |   |
| INSULATOR RESISTANCE:<br>DIELECTRIC                          | 5000MΩ min.   |
| WITHSTANDING VOLTAGE:  | 1000V AC rms  |



|                          | COMBINATION D-SUB                      |  | SW REFERENCE NO.: 630 COMBO ASSEMBLY |        |                    |       |
|--------------------------|--|--|--------------------------------------|--------|--------------------|-------|
| COM                      |  |  | DRAWN: C.B                           |        | DATE: JAN. 01/2019 |       |
|                          |  |  | CHECKED:                             |        | DATE:              |       |
|                          | EDAC INC<br>TORONTO, ONTARIO<br>CANADA | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND<br>SHALL NOT BE REPRODUCED,OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1)               |        | SHEET 1 OF         | 2     |
|                          |  |  | DRAWING NUMBER: 630-7W2-250-3N3      |        | 250-3N3            | ISSUE |
| YOUR CONNECTION TO QUALI |  |  | PART NUMBER: 630                     | )-7W2- | 250-3N3            | 1     |



THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

S

COMPLIANT

