



SS Stainless Steel

Metric table

Dimensions in: millimeters - inches

d <sub>1</sub> Thread	Length l								d <sub>2</sub>	d <sub>3</sub>	h	k
	4	6	8	10	12	16	20	25				
M 2	4 .16	6 .24	8 .31	10 .39	-	-	-	-	9 .35	4.5 .18	5.3 .21	2 .08
M 2.5	4 .16	6 .24	8 .31	10 .39	12 .47	-	-	-	11 .43	5 .20	6.5 .26	2.5 .10
M 3	6 .24	8 .31	10 .39	12 .47	16 .63	20 .79	-	-	12 .47	6 .24	7.5 .30	2.5 .10
M 4	5 .20	8 .31	10 .39	12 .47	16 .63	20 .79	25 .98	-	16 .63	8 .31	9.5 .37	3.5 .14
M 5	6 .24	8 .31	10 .39	12 .47	16 .63	20 .79	25 .98	30 1.18	20 .79	10 .39	11.5 .45	4 .16
M 6	8 .31	10 .39	12 .47	16 .63	20 .79	25 .98	30 1.18	35 1.38	24 .94	12 .47	15 .59	5 .20
M 8	12 .47	16 .63	20 .79	25 .98	30 1.18	35 1.38	40 1.57	-	30 1.18	16 .63	18 .71	6 .24
M 10	12 .47	15 .59	20 .79	25 .98	30 1.18	35 1.38	40 1.57	-	36 1.42	20 .79	23 .91	8 .31

Specification

- Steel
  - Tensile strength class 5
  - Visible face fine turned
  - Blackened finish
  - Zinc plated, blue passivated finish
- Stainless steel
  - European Standard No. 1.4305 (AISI 303)
  - Matte shot-blasted finish
- RoHS compliant

3

ZB

NI

Information

DIN 464 knurled thumb screws are machined from solid bar.

see also...

- Flat Knurled Thumb Screws DIN 653
- Flat Knurled Thumb Screws GN 653.2 (with Recessed Stud for Loss Protection)
- Knurled Screws GN 535 (Stainless Steel)
- Knurled Thumb Screws DIN 464 with Loss Protection GN 111.7

How to order (Steel, blackened)	1 Thread d <sub>1</sub>
DIN 464-M6-20	2 Length l

How to order (Steel, zinc plated)	1 Thread d <sub>1</sub>
DIN 464-M2.5-6-ZB	2 Length l
	3 Finish

How to order (Stainless steel)	1 Thread d <sub>1</sub>
DIN 464-M10-35-NI	2 Length l
	3 Material