



GSM-PRO I/O analogue output module, 4 analogue outputs 0 - 10V, Mounting type: Mounting rail TS 35, Supply voltage range: 20 V - 28 VDC

Business data

Article number	<u>16376.2</u>
Article name	GSM-PRO-4AO
GTIN (EAN)	4044211207762
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	64 g
Weight per piece (including packaging)	66 g
Unit of weight	G
Customs number	85176990
Country of origin	NL
Product description	Controller module

Technical data

Dimensions

Length	95 mm
Width	36 mm
Height	60 mm

Connection data

Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.2 mm ²
Wire cross-section single-core (rigid), max.	4 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	4 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm ²
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm ²
Stripping length	6 mm
Torque	0.4 Nm

Output data

Number of outputs	4
Output type	Analogue
Output signal U/I	0-10 VDC / -
Load resistance U	>1000 Ohm Ohm

Input data

Resolution U (0 ... 10 Vdc)	10bit / ± (30mV + 0,5% of measured value)
-----------------------------	---

Materials

Working temperature, min.	-20 °C
Working temperature, max.	60 °C
Temperature coefficient	<0,02% °C
Relative humidity, max.	90 %

Further technical data

Power supply	20-28 VDC -
Current consumption	57 mA
Protection class	IP20
Storage temperature, min.	-20 °C
Storage temperature, max.	70 °C
Mounting	Mounting rail TS35 / direct mount

Technical data

BUS data

Bus protocol / interface	Modbus RTU / RS485, half-duplex
--------------------------	---------------------------------

Environmental Product Compliance

REACH Conform	yes
---------------	-----

REACH Reference date	2022-06-10
----------------------	------------

REACH Candidate Substance Note	No
--------------------------------	----

RoHS Conform	yes
--------------	-----

Approvals

Standards and regulations


CE compliant

yes

Standards / specifications

Low-Voltage Directive (LVD) 2014/35/EC, in compliance with EN 50178. EMC Directive 2014/30/EC, in compliance with EN 61326-1

Media



Accessories

##INVERSE##CONTA-ELECTRONICS



Compact reporting system for mobile networks to monitor analogue and digital values, and to remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16368.2</u>	GSM-PRO2	4044211207731	1 ST



Compact reporting system for mobile networks to monitor analogue and digital values ??as well as remotely switch relay outputs, incl. GSM positioning, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16408.2</u>	GSM-PRO2E-GPS	4044211219024	1 ST