<u>Mo</u>	unting Option 128 (3.25) Dia. Side Mounting Holes	Contact Detail 500-Wire Hole .087x.013(2.21x0.33) - Tail LG.=.282(7.156 [3.96] Contact Spacing x .140 [3.56] Row Spacing	(.16)	THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.		ISSUE NUM	
	Card Slot Accepts054 (1.37) to .070 (1.78) Thick P.C. Board						
\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	0.156[3.96]	6.092 [154.74] ————————————————————————————————————					
		6.524[165.71]		 1	8.38	d Slot	
	A				0.330	Card Slot	4
[89:					1		SECTION A-
0.460[11.68]	6.524[165.71] 6.834[173.58]				0.125[3.18] Point of Contact		
0			355 Card Edge Connector er: 355-076-500-512		ACAD REFERENCE NO. DRAWN: J.LEE CHECKED:	305 EN DATE: SEF	PT. 21/09
	See Accompanying Page for: Mounting Options		DAC INC NTO, ONTARIO CANADA TY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: NTS DRAWING NUMBER 305 Assembly	SHEET	OF 2 ISSUE

