



SIMATIC ET 200AL, AQ 4xU/I, 4xM12, Degree of protection IP67

Figure similar

General information	
Product type designation	AQ 4xU/I
HW functional status	from FS04
Firmware version	V1.0.x
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version STEP 7 configurable/integrated from version PROFIBUS from GSD version/GSD revision PROFINET from GSD version/GSD revision 	STEP 7 V14 or higher V5.5 SP4 Hotfix 7 or higher GSD as of Revision 5 GSDML V2.3.1
Supply voltage	
power supply according to NEC Class 2 required	No
Load voltage 1L+	
<ul style="list-style-type: none"> Rated value (DC) permissible range, lower limit (DC) permissible range, upper limit (DC) Reverse polarity protection 	24 V 20.4 V 28.8 V Yes; Against destruction; actuator power supply outputs applied with reversed polarity
Input current	
Current consumption (rated value)	110 mA; without load
from load voltage 1L+ (unswitched voltage)	4 A; Maximum value
from load voltage 2L+, max.	4 A; Maximum value
Actuator supply	
Number of outputs	4
Short-circuit protection	Yes; per module, electronic
Output current	
<ul style="list-style-type: none"> Rated value 	Total current 1 A up to 45 °C; 0.5 A up to 55 °C
Power loss	
Power loss, typ.	2.6 W
Analog outputs	
Number of analog outputs	4
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	24 mA
Current output, no-load voltage, max.	15 V
Cycle time (all channels) max.	1 ms
Output ranges, voltage	

<ul style="list-style-type: none"> • 0 to 10 V • 1 V to 5 V • -10 V to +10 V 	Yes; 15 bit Yes; 14 bit Yes; 16 bit incl. sign
Output ranges, current	
<ul style="list-style-type: none"> • 0 to 20 mA • -20 mA to +20 mA • 4 mA to 20 mA 	Yes; 15 bit Yes; 16 bit incl. sign Yes; 14 bit
Connection of actuators	
<ul style="list-style-type: none"> • for voltage output two-wire connection • for voltage output four-wire connection • for current output two-wire connection • for current output four-wire connection 	Yes Yes Yes Yes
Load impedance (in rated range of output)	
<ul style="list-style-type: none"> • with voltage outputs, min. • with voltage outputs, capacitive load, max. • with current outputs, max. • with current outputs, inductive load, max. 	1 k Ω 1 μ F 500 Ω 1 mH
Destruction limits against externally applied voltages and currents	
<ul style="list-style-type: none"> • Voltages at the outputs towards MANA 	16 V
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	30 m
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. 	16 bit
Settling time	
<ul style="list-style-type: none"> • for resistive load • for capacitive load • for inductive load 	1 ms 1 ms 1 ms
Errors/accuracies	
Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-)	0.02 %
Linearity error (relative to output range), (+/-)	0.1 %
Temperature error (relative to output range), (+/-)	0.005 %/K
Crosstalk between the outputs, max.	-70 dB
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.03 %
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> • Voltage, relative to output range, (+/-) • Current, relative to output range, (+/-) 	0.25 % from 55 °C to -25 °C and 0.35 % to -30 °C 0.25 %
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> • Voltage, relative to output range, (+/-) • Current, relative to output range, (+/-) 	0.15 % 0.15 %
Interrupts/diagnostics/status information	
Substitute values connectable	Yes; channel by channel, parameterizable
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	Yes; Parameterizable
Diagnoses	
<ul style="list-style-type: none"> • Wire-break • Short-circuit 	Yes; channel-by-channel, only for output type "current" Yes; Actuator supply module by module; channel by channel for output type "voltage"
Diagnostics indication LED	
<ul style="list-style-type: none"> • Channel status display • for module diagnostics 	Yes; green LED Yes; green/red LED
Potential separation	
between the load voltages	Yes
Potential separation channels	
<ul style="list-style-type: none"> • between the channels • between the channels and backplane bus • between the channels and the power supply of the electronics 	No Yes No

Isolation	
Isolation tested with	707 V DC (type test)
Degree and class of protection	
IP degree of protection	IP65/67
Standards, approvals, certificates	
Suitable for safety-related tripping of standard modules	Yes; from FS04
Highest safety class achievable for safety-related tripping of standard modules	
<ul style="list-style-type: none"> Performance level according to ISO 13849-1 Category according to ISO 13849-1 SIL acc. to IEC 62061 	PL d Cat. 3 SIL 2
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> min. max. 	-30 °C 55 °C
connection method / header	
Design of electrical connection for the inputs and outputs	M12, 5-pole
Design of electrical connection for supply voltage	M8, 4-pole
ET-Connection	
<ul style="list-style-type: none"> ET-Connection 	M8, 4-pin, shielded
Dimensions	
Width	30 mm
Height	159 mm
Depth	40 mm
Weights	
Weight, approx.	175 g
last modified:	3/7/2022 