



Material:

- Cable: UL-2725 [#28(7/0.1 27 T.C)*1P INS:Foam-PE+D.W (7/0.127 T.C)+AL/MY+Hot-melt-Mylar]*2C+#28(7/0.127 T.C)*1P INS:Polyolefin + #28(7/0.127 T.C)*2C INS:Polyolefin + AL/MY +B.D(85%)
 - PVC Jacket
 - OD: 5.2±0.15MM
 - Color: Black
- P1 & P2 Connectors: USB 3.0 B Type Male 9 Pin
 - Contact: 30µ"
 - Shell: Ni-Plated
- Hood: Molded Type, PVC 45P (Black)

PIN OUT	
P1	P2
1 RED	1 PWR
2 WHITE	2 UTP_D-
3 GREEN	3 UTP_D+
4 BLACK	4 GND_PWRrt
5 BLUE	5 SDP1-
6 YELLOW	6 SDP1+
7 D.W	7 SDP1_Drain & SDP2_Drain
8 PURPLE	8 SDP2-
9 ORANGE	9 SDP2+
SHELL	SHELL
	B.D

Electrical:

- 100% Open short & mis wire test
- Contact Resistance: 3Ω Max.
- Insulation Resistance: 10Ω Min.
- Hi-Pot-300V DC

Unit: MM



Scale	1:1						Name
TOLERANCE					Drawn	08.29.11	Chappell
X.X	±0.40				Approved		
X.XX	±0.25						
X.XXX	±0.15						
Angle	±3°						
		Modification		Date	Name		

Item No.	
AK673/3-3	
Title USB 3.0 Cable, B Male <=> B Male, 9 Pin, Insulation Blue, 3 Meters	
Drawing No.	rev00
Replace	Sheet