

ATGBICS SFP-10G-CWDM 1570-40-C network transceiver module Fiber optic 10000 Mbit/s SFP+ 1570 nm

Brand : ATGBICS **Product code:** SFP-10G-CWDM 1570-40-C

Product name: SFP-10G-CWDM 1570-40-C

ATGBICS

R (< today Approximation | 1)

HPE Compatible Transceiver, CWDM SFP+10GBase, 40km, SMF, LC, 1570nm, DOM

ATGBICS SFP-10G-CWDM 1570-40-C network transceiver module Fiber optic 10000 Mbit/s SFP+ 1570 nm:

ATGBICS SFP-10G-CWDM 1570-40 10GBase CWDM supports a distance of up to 40km over single mode fibre (SMF) using a wavelength of 1570nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of HPESFP-10G-CWDM 1570-40= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Features	
Maximum data transfer rate * Interface type * Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector	aximum data transfer rate * 10000 Mbit/s erface type * SFP+ gle-mode fiber (SMF) supported alti-mode fiber (MMF) supported ber optic connector P transceiver standard aximum transfer distance avelength arse Wavelength Division altiplexing (CWDM) bernet interface type glital Diagnostics Monitoring DM) atures aduct colour using material glig and Play t-swap sy to install SFP+ 10000 Mbit/s SFP+ 10000 Mbit/s SFP+ 10000 Mbit/s SFP+ 10000 Mbit/s Silver Metal Indicate the rate of the	Brand compatibility	HP
		Power	
		Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
		Operational conditions	
Maximum transfer distance Wavelength Coarse Wavelength Division Multiplexing (CWDM) Ethernet interface type Digital Diagnostics Monitoring (DDM)		Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height Weight	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95% 13.4 mm 56.5 mm 8.5 mm
Features Product colour Housing material Plug and Play			
Hot-swap		Packaging data	
Easy to install Country of origin		Number of products included Package type	1 pc(s) Box
		Technical details	
		Sustainability certificates	RoHS



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.