
THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER. .X ±0.25


.XX ±0.13 .XXX ±0.05



ISSUE NUMBER	
ORIGINAL	

(1)






NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:


THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, 30µ" GOLD PLATED



SIGNAL CONTACT RESISTANCE:	10mΩ MAX.
SIGNAL CONTACT CURRENT RATING:	5A PER CONTACT
(IF PRESENT)	· · · ·
POWER/CO-AX CONTACT RATING:	20A (CURRENT)
OPERATING TEMPERATURE:	-55°C ~ 125°C

**INSULATOR RESISTANCE:** DIELECTRIC WITHSTANDING VOLTAGE: 5000MΩ min.

1000V AC rms



			SW REFERENCE NO.: 629 COMBO ASSEMBLY		
ļ	COMBINATION	COMBINATION D-SUB		DATE: JAN. 01/201	19
ļ			CHECKED:	DATE:	
Г	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
ļ	TORONTO, ONTARIO CANADA	OR USED AS THE BASIS FOR THE	DRAWING NUMBER: 629-9W4-	-640-2T6	ISSUE
YOU	YOUR CONNECTION TO QUALITY & SERVICE	MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUMBER: 629-9W4-	-640-2T6	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

